

## “BIG FRIGGIN” (BFL) SERIES LIFTS

*The BFL series lifts were designed for high travel applications that also require large platforms. These lifts are designed to move multiple pallets or large loads between floors or to high mezzanines. These big lifts are all built with tubular steel legs to maximize the rigidity of the unit and to keep the weight down.*



### SPECIAL FEATURES & BENEFITS

- ▶ These units are equipped with the patented “Platform Centering Device”.
- ▶ All of the controllers are assembled in our UL listed panel shop.
- ▶ These units are fully primed and finished with a baked enamel finish.
- ▶ The cylinders are machine grade with return lines.
- ▶ The oil reservoirs are mild steel for long life.
- ▶ These units conform to all applicable ANSI codes.
- ▶ All pressure hoses are double wire braid with JIC fittings.

\*shown with optional hand rail

### FEATURE DETAILS



▶ *Patented Platform Centering Device*



▶ *BFL Cylinder w/Clear Plastic Return Lines*



▶ *Power Unit w/Controller*



▶ *Double Wire Braid Hose*



▶ *BFL Swing Arm Safety Bar*

# "BIG FRIGGIN" (BFL) SERIES LIFTS

## SPECIFICATION TABLE FOR BFL SERIES LIFTS

Model	Travel	Capacity	Std. Min. Platform	Opt. Max. Platform	Maximum End	Loading Side	Baseframe Size	Lowered Height	Raised Height	Speed Sec.	Motor H.P.	Ship Wt.
BFL2-2120	120	2000	72 X 96	96 X 120	1100	625	72 X 96	14-1/2	134-1/2	45	2	2,130
BFL2-4120	120	4000	72 X 96	96 X 120	2150	1325	72 X 96	15-1/2	135-1/2	47	5	2,607
BFL2-6120	120	6000	72 X 96	96 X 120	3150	1825	72 X 96	17-1/2	137-1/2	45	5	2,653
BFL2-2144	144	2000	72 X 108	96 X 132	1300	700	72 X 108	15-1/2	159-1/2	54	2	2,521
BFL2-4144	144	4000	72 X 108	96 X 132	2550	1325	72 X 108	17-1/2	161-1/2	48	5	3,085
BFL2-6144	144	6000	72 X 108	96 X 132	3500	1925	72 X 108	17-1/2	161-1/2	57	5	3,767
BFL3-2180	180	2000	72 X 96	96 X 120	1325	600	72 X 96	20	200	65	2	2,855
BFL3-4180	180	4000	72 X 96	96 X 120	2650	1200	72 X 96	23	203	67	5	3,930
BFL3-6180	180	6000	72 X 96	96 X 120	4000	1950	72 X 96	26	206	71	5	3,990
BFL3-2216	216	2000	72 X 120	96 X 144	1325	800	72 X 120	26	242	82	2	5,065
BFL3-4216	216	4000	72 X 120	96 X 144	2650	1025	72 X 120	26	242	78	5	5,065
BFL3-6216	216	6000	72 X 120	96 X 144	4000	2650	72 X 120	32	248	82	5	6,954

## OPTIONS:

### ELECTRICAL:

- ▶ Wall mounted push-button
- ▶ Up, down, stop circuits
- ▶ Limit switches

### MECHANICAL:

- ▶ Hand rails
- ▶ Enclosures

## WARRANTY:

### ADVANCE LIFTS WARRANTY:

For a period of one (1) year from date of shipment from the Company's plant, the Company agrees to replace or repair, free of charge, any defective parts, material or workmanship on new equipment. This shall include electrical and hydraulic components.

For a period of ten (10) years or 250,000 cycles (whichever occurs first) from date of shipment from Company's plant, the Company agrees to replace or repair any defective structure.

Company authorization must be obtained prior to the commencement of any work. The Company reserves the right of choice between effecting repairs in the field or paying all freight charges and effecting the repairs at the Company's plant. The Company further reserves the right of final determination in all warranty considerations. Evidence of overloading, abuse or field modification of units without Company approval shall void this warranty. No contingent liabilities will be accepted.