

SkyGuard™

Skylight Protection System

Meets OSHA Requirements

1926.501(b) (4) CAL OSHA 3209(b)

Modular system for OSHA compliant fall protection around skylights and other openings. Ideal for venting or smoke-hatch skylight protection. Galvanized bases for resistance to the elements. Rails available in yellow.

- Affordable Protection
- Standard and custom sizes available.
- Freestanding design maintains watertight integrity.
- Galvanized to resist corrosion.
- Rubber foot pads to prevent sliding or damage to membranes.
- Easy to transport and assemble making it well suited for temporary job site protection.



Why Choose Garlock?

- Rigorously Tested to Exceed OSHA & ANSI Standards
- In-House Engineering
- 100+ Years of Industry Experience
- Full Passive Fall Protection Portfolio
- Custom Engineered Products Available



Features



Galvanized wide Base free-stands on roof.



Quick bolt together assembly.

Specifications

- Posts and bases galvanized.
- Rubber footpads Included
- Top rail height = 42"
- Lower rail height = 20"
- Rails are yellow powdercoated.
- Custom sizes also available.

Standard Sizes	L	W	H
4848	54"	54"	42"
4896	102"	54"	42"
9696	102"	102"	42"

*Due to continuous improvement, specifications are subject to change without notice.

GARLOCK
SAFETY SYSTEMS

For assistance, contact

Cisco-Eagle

1-888-877-3861

www.cisco-eagle.com