

VINYL ROLL-UP • BUG BLOCKING MESH • VINYL ROLL-UP • BUG BLOCKING MESH • VINYL ROLL-UP • BUG BLOCKING MESH

VINYL ROLL-UP • BUG BLOCKING MESH • VINYL ROLL-UP • BUG BLOCKING MESH • VINYL ROLL-UP • BUG BLOCKING MESH



GRAVITY FEED MOTORIZED VINYL ROLL-UP DOORS

Travel Speeds 6-36 IPS

From the Makers of *Goff's* The Original



*RF Versions Only

Benefits

- Reduces Heat Loss
- Clear Window Allows Light Into Work Areas
- Portable Wireless Door Controls Attach to Forklift, Keeping the Operator from Having to Abandon the Vehicle to Open the Door*
- Wireless Control Stations Control the Roll-Up Door from Multiple Locations*
- Reduce Noise from Adjacent Areas
- Control Airborne Contaminants
- Separate Inside Work Areas
- Discourage Intruders When Product is Used on Outside Door Applications



Features

- Double Baffle, under valance, prevents debris and pests from entering
- Valance Panel made from 18-oz coated vinyl helps to keep debris and pests out while protecting the roller tube
- Fiberglass Pultrusion Tube (Horizontal Stiffeners) bend if loaded – won't break or kink (see photo below)
- Rugged Custom Extruded Guide Track traps the rollers–wind can't blow it out of the doorframe
- Pultrusion Pockets are reinforced with additional 18-oz coated vinyl and double lockstitched for durability
- 18-oz Coated Vinyl with 40-mil. Double Polished Window meet California Fire Marshal Standards for Flame Retardancy, while standing up to the harshest of weather


Chain Hoist Operation

- Rolls Up & Down Easily
- Adjustable Stops
- Lockable




Pultrusion Pocket

- All Seams Double Lock Stitched for Extra Strength
- Pultrusion Pockets are Reinforced with an Extra Layer 18-oz Material Adding Extra Strength and Toughness



Extrusion

- Custom Extruded Track with Reinforced Section
- Rollers are Trapped in an Extruded Cavity
- Heavy Duty Rollers Provide Smooth Operating Motion



EPDM Seals on Both Sides Ensure a Tight Seal at Vertical Edges.



- Breakaway Feature Prevents Damage To Door or Guide Track
- Easy to Reset Back Into the Track



In Tube Motor

- 110-Volt Operation
- Limit Switch Controls Up and Down Position
- 6"/Second Travel Speed
- Optional 12"/Second High Speed
- 40% Duty Cycle



In Tube Spring

- Adjustable Torque Settings
- Start-Stop at Multiple Positions



Chain Hoist Operation

- Start-Stop at Multiple Positions
- Lockable
- Rolls Up and Down Easily



External Mounted Motor

- 36"/Second Travel Speed
- 4000 Cycles per Day
- 110 Volt Operation
- Chain Hoist Override



Sizes Available (x)

Size W' x H'	Motorized	Spring Assist
8' x 8'	(x)	(x)
8' x 9'	(x)	(x)
8' x 10'	(x)	(x)
9' x 9'	(x)	(x)
9' x 10'	(x)	(x)
10' x 8'	(x)	(x)
10' x 10'	(x)	(x)
10' x 12'	(x)	(x)
10' x 14'	(x)	(x)
12' x 10'	(x)	(x)
12' x 12'	(x)	(x)
12' x 14'	(x)	(x)
14' x 14'	(x)	(x)
14' x 15'	(x)	(x)

Custom Sizes Available.

Mounting Options:

Under Header Mount attaches to the underside of doorframe.



Inside or Outside Mount attaches to opening's face.

Operation Control Options:



3 Position Toggle Switch
(Standard for In Tube Motor)



Handheld Remote Control



Nema 1 (Interior Use) Hard Wired Control



Nema 4 Hardwired Indoor/Outdoor Wall Mounted Control



Nema 4 (Exterior Use) Hard Wired Control



Nema 4 (Exterior Use) Locking Hard Wired Control



Pull Cord (Indoor/Outdoor)

Choose From 7 Different Colors:



Warranty

3-year limited warranty on materials and workmanship. Warranty excludes electric motor and spring-assist roll-up mechanism; warranty on these items is 1 year. Goff's reserves the right to repair or replace warranty items at its discretion.

Sold Through Distributors Everywhere! Call To Find Your Nearest Goff's Distributor


Goff's Other Products



Curtain Walls



Privacy/Security Screens




Weldview Screens



Sound Barriers



Privacy/Security Curtains



Weldview Curtains



Strip Doors



Goff's Enterprises, Inc., 1228 Hickory Street, Pewaukee, WI 53072
 e-mail: sales@goffscw.com • www.industrialcurtains.com
 Phone: (262) 691-4998 • 800-234-0337; Fax (262) 691-3255 • 800-959-0170