

1228 Hickory St.
Pewaukee, WI 53072
Telephone: (262) 691-4998
Fax: (262) 691-3255
Email: candi@goffscw.com
www.goffscurtainwalls.com

Goff's Enterprises, Inc.

Amber Weld Screen

Product Specifications

Thickness: .080"
Width: 8"
Finish: Double Polished
Color: Amber

| Property | Result | ASTM |
|--------------------------|---|-------|
| Hardness (15 sec delay) | 83 A Scale | D2240 |
| Tensile Strength | 2800 PSI | D412 |
| Ultimate Elongation | 330% | D412 |
| Graves Tear | 280 | DI004 |
| 100% Modulus | 1450 PSI | D412 |
| Brittleness Temp | -34° F | D746 |
| Operating Temp | 0° F to 150° F | - |
| Specific Gravity | 1.25 | D792 |
| Density | 75lbs cu. ft. | C-177 |
| Thermal Conductivity (K) | .73 | C-177 |
| Thermal Resistance (R) | 1.37 | C-177 |
| UV Resistance | Yes | |
| Flammability Rating | Compliant w/ California State Fire Marshall | |

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

Manufacturers of The Original Goff's Curtain Walls

"Where Quality Value & Service Become One"