



**ILLINOIS  
ENGINEERED  
PRODUCTS**

# Portable Gate Barrier Gate | Aisle Gate



- *Moveable access control and security*
- *High visibility*
- *Reduce liability occurrences*
- *Use one gate in multiple locations*

**100% MADE IN  
AMERICA**

THE ONLY FOLDING GATES MADE WITH GALVANIZED STEEL

**54 YEARS**  
OF INNOVATION,  
QUALITY & SERVICE

# Portable Gate

## Galvanized Steel

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Starter XL1265	up to 12'	6'6"	6'	135
Add-on XL665	adds 6'	6'6"	6'	64

### Specifications

**Finish:** Galvanized steel.

**Webbing:** 14 gauge 3/8" x 3/4" u-channel riveted back to back with zinc plated rivets.

**Vertical Frame:** 12 gauge 1-1/2" x 1-1/2" angle.

**Axles:** 28" wide with 3" locking rubber casters.

**Locking:** Padlock hasp. Can be locked in place with wallmounted locking bars.

**Starter:** May be used alone, or to start a run of gates.

**Add-on:** Attaches to Starter Gate providing an additional 6' in width. Unlimited Add-on gates can be connected to a Starter Gate.

**Options:** Powder coating color; 7' in-use height gate and 8' in-use height gate, special order.

## Aluminum

Call factory for specifications.

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Starter XL1265AL	up to 12'	6'6"	6'	75
Add-on XL665AL	adds 6'	6'6"	6'	32

## Portable and Barrier Gate Accessories

**Padlock:** 2" hardened steel with plated shackle.

**8' Post:** Lock gate to posts instead of wall or casing.



Starter Portable Gate



Starter Barrier Gate



Aisle Gate

Illinois Engineered Products are only sold by Authorized Dealers



# Barrier Gate

## Galvanized Steel

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Starter XL1240	up to 12'	47"	41"	90
Add-on XL640	adds 6'	47"	41"	40

### Specifications

**Finish:** Galvanized steel. Powder coated yellow & black.

**Webbing:** 14 gauge 3/8" x 3/4" u-channel riveted back to back with zinc plated rivets.

**Vertical Frame:** 12 gauge 1-1/2" x 1-1/2" angle.

**Axles:** 14" wide with 3" locking rubber casters.

**Locking:** Padlock hasp. Can be locked in place with wallmounted locking bars.

**Starter:** May be used alone, or to start a run of gates.

**Add-on:** Attaches to Starter Gate providing an additional 6' in width. Unlimited Add-on gates can be connected to a Starter Gate.

**Option:** Other powder coating colors.

## Aluminum

Call factory for specifications.

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Starter XL1240AL	up to 12'	47"	41"	45
Add-on XL640AL	adds 6'	47"	41"	20

# Aisle Gate

## Galvanized Steel

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Aisle Gate	7'	40"	40"	12

### Specifications

**Finish:** Galvanized steel. Powder coated yellow.

**Webbing:** 14 gauge steel 3/8" x 3/4" u-channel riveted back to back with zinc plated rivets.

**Vertical Frame:** 12 gauge steel 1-1/2" x 1-1/2" angle.

**Feet:** 14" wide.

Multiple Aisle Gates can be hooked together to form corners or any length. Light weight and welded on handle makes it easy to move from area to area.

## Aluminum

Call factory for specifications.

Stock No.	Maximum Width	Collapsed Height	In-Use Height	Weight (lbs.)
Aisle Gate-AL	7'	40"	40"	6

