

THORK-LIFT HL

– benefits and features

High efficiency = high performance

- The working height can be adjusted
- * Two lifting speeds can be selected
- Great manoeuvrability
- Neutral position = Great manoeuvrability
- * Capacity 3300 lbs to lifting height 18.5 inches
- * Low own weight

High safety

- * Central location of control buttons
- * Foot protection
- * Low overall height
- Supporting stabilisers at steering wheels
- * Tandem wheels on scissors legs
- * Patented reliable cylinder construction (with ball lock)
- * Low noise level (fine tolerances and rubber softened wheel holder)
- 47 inch forks ensure optimum support for the pallet
- * Brake at fork wheel = optimum stability
- * Fulfils all CE requirements

Optimum ergonomics

- * Ergonomically correct handle
- Lift height adjustable to individual requirements (reduces strain on back and shoulders)
- * Rounded corners meaning less damage to surroundings

Great durability = low costs

- Long operating life
- * Low maintenance costs (simple construction, easy to replace parts)
- Strong construction
- * Use of quality materials
- Cylinder construction with twin seals
- * Pump unit with special oil for long durability

High flexibility

- * Many different fork lengths and width
- * Tailor-made solutions
- * Available in stainless plus and semi stainless versions
- * Available in explosion proof version
- * Available in antistatic version
- Different wheel materials available
- Available with electric lifting (EHL)



Features marked with * are unique for the Interthor products