

Insulated Curtain Wall - InsulWall®

- Effectively create temperature-controlled areas
- Easy to install – attaches to roof decks, joists, beams, and more
- Panels joined by commercial-grade Velcro®
- Modular and moveable

	IW- 3 GREEN	IW- 6 GREEN	IW- 9 GREEN	IW- 15 GREEN
Degrees of Separation	Up to 15°F (Up to 9° C)	Up to 25°F (Up to 14° C)	Up to 35°F (Up to 19.5° C)	Up to 40°F (Up to 22° C)
R-Value	R-3	R-6	R-9	R-15
Panel Width	5' wide	5' wide	5' wide double-wall	5' wide double-wall
Core	Recycled	Recycled	Recycled	Recycled
Weight	.34 lbs/sq ft	.40 lbs/sq ft	.68 lbs/sq ft	.80 lbs/sq ft
Exterior Flame Resistance	Exterior ASTME84 Class A	Exterior ASTME84 Class A	Exterior ASTME84 Class A	Exterior ASTME84 Class A

These marketing materials, including the above chart do not constitute representations or promises by Randall Manufacturing, LLC that the InsulWall® products will attain the performance values depicted therein after installation in the field. The actual values for "R Value" and "Degrees of Separation" may vary in actual field application, depending on usage and environmental factors, including but not limited to room layout, capacity of refrigeration equipment, number of door openings, and building insulation installed. The customer is directed to consult a refrigeration specialist to ensure that a particular installation of InsulWall® will meet the particular requirements of the field application for which it was intended.