

IQ

P L U S

3 5 5

DIGITAL WEIGHT INDICATOR



ANOTHER **REVOLUTION**™ SOLUTION
SCALE SOFTWARE

THE IQ PLUS® 355...
UNPARALLELED PERFORMANCE AND VALUE.

RICE LAKE WEIGHING SYSTEMS
Industrial Solutions on a Global Scale®



IQ

P L U S

3 5 5

DIGITAL WEIGHT INDICATOR



The IQ plus® 355...High Performance, High Durability, Low Price.

The IQ plus 355 is built to outlast and outperform any other indicator in its class. It's the only true industrial scale product in its price category.

Providing the ultimate protection, the IQ plus 355 is encased in a tough, all stainless steel NEMA 4X/IP66 enclosure for extra-long life, even in the harshest conditions. The Firelite™ ultra-bright, oversized display reduces operator error and accelerates productivity.

Fully interactive, the IQ plus 355 features two independent communication ports for complete EDP and print ticket programmability. It easily programs two formats with up to 300 characters, allowing you to create complex custom tickets.

The IQ plus 355 drives up to 8 350-ohm load cells, making it the perfect choice for simple multi-cell applications. Additionally, it features RATTLETRAP™ three-stage digital filtering for eliminating most vibration interference and providing stable, accurate weight data regardless of environment. A simple five-button front panel provides easy operation with full calibration and configuration.



Standard Features:

- Large .8" (20.3mm) Light Emitting Diode (LED) display
- Primary/secondary units configuration: lb, kg, ounce, short tons, metric tons, grams, or none
- Stainless steel washdown enclosure
- 5-button operation
- 2 independent communication ports
- Power for 8 350-ohm load cells or 16 700-ohm load cells
- Three-stage digital filtering
- 2 x 300-character programmable print formats
- Consecutive numbering
- Universal mounting stand
- 2 digital inputs

Options:

- Analog output: selectable 0-10V, 4-20mA
- Panel mount kit

Specifications:

Display:	0.8" (20.3mm) LED 6-digit
Annunciators:	Gross, net, zero, motion, lb, kg, oz, g
Power:	115 VAC @ 70 mA, or 230 VAC @ 35 mA, 50-60 Hz
Load Cells:	8 x 350-ohm, 16 x 700-ohm
Internal Resolution:	308,000 internal counts
External Resolution:	100,000 display divisions
System Linearity:	Within 0.01% of full scale
Measurement Rate:	Configurable 30, 15, 7, 3 updates/second
Filtering:	RATTLETRAP™ three-stage digital filtering
Serial Ports:	Two independent outputs, (1) full duplex RS-232: (1) simplex RS-232 or 20mA
Consecutive Number:	Selectable start point of "0" or "1" to 999,999
Radiated Immunity:	3 volts/meter EN 61000-4-3
ESD Immunity:	IEC 801-2:91 EN 61000-4-2 per EN 45501
Digital Inputs:	Two configurable digital inputs
Enclosure:	NEMA 4X/IP66
Enclosure Size:	9.5" x 6" x 2.75" (241.3mm x 152.4mm x 69.9mm)
Temperature Range:	Legal for trade: -10°C to +40°C/14°F to 104°F
Warranty:	2-year warranty
Approvals:	NTEP certified per H-44 at 10,000 Divisions, Class III/III L, CC# 97-130A2. Measurement Canada approved, AM-5213, Class III/III HD at 10,000 divisions. OIML approved TC6008. UL and CUL listed, CE marked.



MEASUREMENT CANADA
AM-5213
n_max = 10,000
Class III/III HD



The IQ plus 355 provides two print formats that can be customized to include up to 300 characters on printed tickets.

Your Rice Lake Weighing Systems distributor is:

RICE LAKE WEIGHING SYSTEMS
Industrial Solutions on a Global Scale®

230 W. Coleman St. • Rice Lake, WI 54868 • USA
TEL: 715-234-9171 • FAX: 715-234-6967 • WEB SITE: www.rlws.com

© Rice Lake Weighing Systems 2002 PN 53052 6/02
Specifications subject to change without notice