



## CW-90 & CW-90X

With the CW-90/90X's operator-friendly software, simply place your product or target weight on the scale, press "target," and you're ready to checkweigh. The bright, oversized LED display and vibrant "Under," "Over" and "Accept" lights provide the operator with necessary information at a glance.

**RICE LAKE**  
WEIGHING SYSTEMS

Commitment Beyond Measurement®

230 W. Coleman St. • Rice Lake, WI 54868 • USA  
TEL: 715-234-9171 • FAX: 715-234-6967  
[www.ricelake.com](http://www.ricelake.com)

© 2009 Rice Lake Weighing Systems PN 109423 3/09  
Specifications subject to change without notice

## Rice Lake Checkweigher Matrix

	CW-90X	CW-90	CW-80	IQ plus® 2100
<b>Load Cell</b>	Stainless Steel, Hermetically Sealed, IP69K, NTEP 1:5000	Aluminum, NTEP 1:5000	Stainless Steel, IP67, NTEP 1:3000	Aluminum, NTEP 1:5000
<b>IP Rating on Indicator</b>	IP69K	IP66	IP66	IP66
<b>Keypad Construction</b>	Piezo	Membrane	Piezo	Piezo Switches
<b>Gore® PreVent Breather Vent</b>	Standard	Standard	No	Standard
<b>Configurable with Revolution® III</b>	Standard	Standard	No	Standard
<b>Configurable Print Format</b>	Standard	Standard	No	No
<b>Audit Trail</b>	Standard	Standard	No	No
<b>Approvals</b>	<b>Indicator:</b> NTEP, Measurement Canada <b>Indicator Pending:</b> UL/CUL, CE, OIML <b>Base:</b> NTEP, Measurement Canada <b>Base Pending:</b> OIML <b>Indicator/Base as System:</b> NSF	<b>Indicator:</b> NTEP, Measurement Canada <b>Indicator Pending:</b> UL/CUL, CE, OIML <b>Base:</b> NTEP, Measurement Canada <b>Base Pending:</b> OIML <b>Indicator/Base as System:</b> NSF	<b>Indicator:</b> NTEP, Measurement Canada, UL/CUL, European Approval, EC Type Approval, OIML <b>Base:</b> NTEP, Measurement Canada	<b>Indicator:</b> NTEP, Measurement Canada, UL/CUL <b>Base:</b> NTEP, Measurement Canada
<b>Time and Date</b>	Standard	Standard	No	No
<b>ID Storage</b>	50 (target, over, under, tare, unit of measure, description 1, description 2)	50 (target, over, under, tare, unit of measure, description 1, description 2)	300 (over, under, tare, unit of measure)	No
<b>Ethernet</b>	Wired or Wireless with Option Card	Wired or Wireless with Option Card	No	No
<b>Fiber Optics</b>	With Option Card	With Option Card	No	No
<b>USB</b>	With Option Card	With Option Card	No	No
<b>Digital I/O on CPU Board</b>	4 Configurable I/O	4 Configurable I/O	Optional, Requires Different CPU	Two Digital Inputs for Remote Zero, Print and Units
<b>LED Display</b>	0.8in (20.3mm)	0.8in (20.3mm)	0.8in (20.3mm)	0.8in (20.3mm)
<b>Test Menu</b>	Standard	Standard	No	No
<b>Custom Software Available</b>	Consult Factory for Quote	Consult Factory for Quote	No	No
<b>Warranty</b>	3 Year Limited	2 Year Limited	2 Year Limited	2 Year Limited
<b>Power for up to (8) 350 Ohm Load Cells</b>	Standard	Standard	Standard	Standard
<b>Updates Per Second</b>	Adjustable 7.5 to 960	Adjustable 7.5 to 960	25	3.76
<b>DC Power Supply</b>	9-36VDC Option	9-36VDC Option	No	No
<b>Ability to Upgrade Software in the Field</b>	Standard	Standard	No	No