

Trachte Product Details

Portable Self-Storage Container



p: 800-356-5824 f: 800-981-9014
w: trachte.com e: tbs@trachte.com
314 Wilburn Road, Sun Prairie, WI 53590-1469

TBS TRACHTE
Building Systems

Trachte™ Portable Self-Storage Container



PRODUCT SPECIFICATIONS

STACKABLE MODELS

Can be stacked 2 containers high, loaded
(must be indoors on level, solid ground)

Capacity

5': 2000 lbs
12': 4800 lbs

Container Weight (empty)

5': 1600 lbs
12': 2500 lbs

Door Opening

6'5" width x 6'4" height
(measured with door installed, sill to door bottom)

Height

Interior:
7'6" from deck to bottom of roof joists
Exterior:
9'0" including wheels and stacking channels

Base width

89"

Floor System

3/4" treated plywood on 12-gauge joists,
16" OC

NON-STACKABLE MODELS

Capacity

12': 4800 lbs
16': 6400 lbs

Container Weight (empty)

12': 2375 lbs
16': 3250 lbs

Door Opening

12': 6'5" width x 6'4" height
16': 6'5" width x 6'5" height
(measured with door installed, sill to door bottom)

Height

Interior:
12': 7'6" from deck to bottom of roof joists
16': 7'8" from deck to bottom of roof joists
Exterior:
8'10" including wheels

Base width

89"

Floor System

12': 3/4" treated plywood on 12-gauge joists, 16" OC
16': 3" x 2" x 1/8" steel tubing, 16" OC

Note: Product specifications are subject to change without notice.

PRODUCT DESCRIPTION

OVERVIEW

The Trachte Portable Container is designed to provide the independent business owner with a low-risk opportunity to expand and diversify their current business--without the burden of franchise royalties or dealership fees. Trachte offers a variety of container models: 5' stackable, 12' stackable, 12' non-stackable, and 16' non-stackable.

SHIPPING & ASSEMBLY

The steel containers are shipped unassembled in kit form, which allows for more units to be loaded per truck and reduces shipping costs. Detailed instructions outline the assembly of the container and are included with every order. Typical assembly per container takes two people one day. Contact Trachte for a list of qualified contractors to assemble the containers, if needed.

GENERAL FEATURES

The Trachte Portable Container features a sturdy steel frame to ensure strength and rigidity. Load bearing wall studs, floor and roof joists, and frame rails are made from thick 12-gauge hot-dipped galvanized steel or painted structural steel. Our wall studs feature industry standard sized "E-track" slots for tie downs, making it easy to secure contents. On the exterior, heavy duty "D" rings provide a solid point to secure the container to the truck for transport. On the stackable models, raised channels on the rooftop allow the stacked containers to rest directly on their frame rails with their wheels suspended.



The container's 18-gauge steel exterior is available in the same four colors as Trachte's traditional self-storage buildings and provides a smooth surface for signage. Floor decking is 3/4" treated plywood with a steel threshold, preventing damage to the door sill. A low loading height eliminates the need for ramps or lifts during loading.

The container is built to withstand all weather conditions, keeping contents dry while providing ventilation to prevent heat buildup and condensation. A draftstop at the top of the door reduces dust and snow intrusion. No tarp is needed for outdoor storage. A 1-year warranty protects against defects in materials and workmanship.

The Portables also feature Trac-Rite roll-up doors for easy loading. These worry-free doors are available in 10 colors to help you brand your business. A SpaceGuard latch is standard on every door and offers provisions for a cylinder lock and two padlocks.

Trachte™ Portable Self-Storage Container



5' SPECIFIC FEATURES

We built our little container with big thinking: as in a big door, taller height for easier loading, and more overall cubic storage space than many other containers with the same footprint. Other containers of the same size normally place the door on the 5' side, rather than on the long side. Our unit may be lifted from any side, saving your staff valuable material handling time. This smaller-sized container is designed to work with truck mounted forklifts for flexible delivery in tight spaces.



12' and 16' SPECIFIC FEATURES

To give our larger containers extra strength, a welded steel subframe is incorporated into the design. The subframe supports the wheels, keeps the container square, and provides reliable connections for winching and tie downs. The 12' model utilizes two frames (one at each end), while the 16' model utilizes a full-length welded frame for added support.



Transporting and handling containers can be a challenge when it comes to large-sized units. While some container systems require the purchase of elaborate proprietary lifts, our containers are intended for use with common rollback trucks. To minimize damage to pavement and rollback truck beds, we've equipped the larger Trachte containers with 8" diameter x 6" wide steel wheels. Containers with wheels may be subject to less restrictive local ordinances regarding placement.



STANDARD DOOR COLORS

CEDAR RED	GARNET
ICED WHITE	SUNSET ORANGE
EVERGREEN	ROYAL BLUE
DESERT TAN	SHALE
CONTINENTAL BROWN	POLAR BLUE

WALL COLORS

SLATE GRAY	ICED WHITE
CREAM BEIGE	CLASSIC BEIGE

Note: Colors shown are printed samples on paper. Colors vary from actual panel material. For a steel color sample, please contact Trachte Building Systems at 800-356-5824.



800.356.5824

For more information on Trachte
self-storage systems, please contact us:

800-356-5824
trachte.com