



DOCK LOADING LIGHT INSTALLATION INSTRUCTIONS



120VAC MODELS

MOUNTING:

- Select a location and drill four holes using the drill template included. Be sure to select the proper hole pattern for the model being installed. Recommended mounting height is 6-½ feet
- For solid surfaces: 3/8-inch lag bolts with appropriate expansion anchors are recommended. For hollow walls with no rear access, toggle bolts with expansion wings are recommended. For hollow wall with rear access, use 3/8-inch bolts, washers, lock washers and nuts.
- Secure lamp head assembly to the end of the lamp arm.

MODELS with VERTICALLY ADJUSTABLE LAMP ARMS (Models SDL and DSDL)

Sufficiently tighten the nut and bolt that holds the lamp arm to the swivel bracket so that the lamp arm remains in place.

Warning:

- **Wire guards or grilles are UL required components, providing openings to avoid excessive heat buildup. Promptly replace damaged or missing wire guards or grilles.**
- **Using excessive wattage bulbs may cause the lamp heads to overheat resulting in melted lamp heads or fire. The maximum wattage bulb that can be used in a lamp head is:
For Metal Head- 300 watt incandescent bulb
For Plastic Head- 150 watt incandescent bulb
(PAR 38 type lamps have been found to be the most durable type of incandescent bulb.)
For HPS Head- 50 watt HPS bulb. CAUTION: All HPS Power: 120 v. 60 Hz ONLY**

SERVICING POLYCARBONATE FIXTURES:

- Do not over-tighten the lamp adjustment screws.
- For HPS models with a metalized reflector, use a clean, damp cloth on surfaces to avoid scratching the reflecting surface.

REPLACEMENT PARTS (see: www.triliteinc.com/documents.htm for more details)

PART NUMBER	DESCRIPTION
INCHEAD	Metal lamp fixture for incandescent bulbs, complete
DLWG6	Wire guard for metal lamp fixtures
733026	Power cord connecting metal lamp fixture to arm
INCHEAD-P	Polycarbonate lamp fixture for incandescent bulbs, complete
DLWG8-P	Wire guard for polycarbonate incandescent lamp fixtures
733024	Power cord connecting polycarbonate lamp fixture to arm
413150	Lamp socket for polycarbonate and metal lamp fixtures
HPSHEAD-P	Polycarbonate lamp fixture with reflector for High Pressure Sodium lamps, complete
203003Y	High Pressure Sodium polycarbonate diffuser grill
HPSFS	High Pressure Sodium diffuser grill assembly and clear polycarbonate food service cover
413000	High Pressure Sodium lamp socket
423001	50 watt High Pressure Sodium lamp Type LU 50
443000	High Pressure Sodium lamp igniter
623000	High Pressure Sodium lamp ballast
DLFAN	18" diameter 3-speed Fan with adapter power cord
103567	U-shaped lamp fixture attachment bracket for all models
403003	On/Off switch for all models
413019	In-arm power receptacle for all models
733016	Power cord for 24", 40" and 60" models
733014	Power cord for 90" and 114" models