

Product Data Sheet

Item Number: 1230 / 1231

Item Name: Ultra-SpillPallet P4, Nestable Model

Load Capacity UDL

- 6000 lbs./each (2721.6 kg/each)

Sump Capacity

- 66 gal./each (249.8 L/each)

Item #	Color	Misc. Features	Amount	Length	Width	Height	Weight	Qty/Pallet
1230	Yellow	No Drain	1 each	51" (129.5cm)	51" (129.5cm)	10" (25.4cm)	80lbs. (36.3kg)	10
1231	Yellow	With Drain	1 each	51" (129.5cm)	51" (129.5cm)	10" (25.4cm)	80lbs. (36.3kg)	10

Description

A polyethylene sump with deck surface large enough to store four 55-gallon drums. In the event of a leak, fluid is contained in the sump preventing contamination to surrounding environment.

Application

For storage of both steel and polyethylene drums and smaller containers which need to meet containment regulations and/or for general housekeeping purposes.

Product Features

The Ultra-SpillPallet P4, Nestable Model helps you comply with containment regulations while storing steel and poly drums. Capture leaks, drips and spills to keep floors dry and workers safe.

- 6,000 lbs. UDL capacity is strong enough to support four fully loaded steel or poly drums
- Molded-in sump catches leaks, drips and spills to help you comply with regulations and keep your storage areas clean and safe
- Low 10" height means loading and unloading require less effort and drum tops are within easier reach
- Compact footprint reduces floor area needed for drum storage
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals for long, trouble-free life
- Removable textured grating enhances traction to minimize costly slips and to help

- prevent drums from sliding; lifts out to provide unrestricted sump access for hassle-free cleaning
- Optional drain plug lets you conveniently empty sump without removing drums or grating
- 2-way forklift entry allows easy movement from either direction (unloaded only)
- Nestable design permits stacking when not in use to save space; lowers cost of bulk shipping

Composition

- 100% Polyethylene (LDPE) with UV inhibitors.

This product helps you comply with:	
Regulatory Citation	Summary
40 CFR 112.7	SPCC planning requirements state that facilities subject to these regulations must have written plans in place discussing the products, countermeasures and procedures that are in place, or will be taken by the facility to prevent discharge of oil into waters of the United States.
40 CFR 264.175	Hazardous waste containment systems must be free of structural cracks or gaps, be designed to keep spilled liquids from remaining in contact with the container, prevent run-on and "have sufficient capacity to contain 10% of the volume of the containers, or the volume of the largest container, whichever is greater."

Additional Specifications

- Dimension(Grate) : 48"L x 48"W

Disclaimers

Flammables Notice: If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources.

