



Note: If units must conform to seismic requirements, use all Starter units, with tie plates and footplates.


Assembly Instructions for RiveTier Tire Rack




LURHD
Upright Angle




SS
Shelf Support Beam




TSS
Tire Rack Beam




WT
Wall Tie



AT
Aisle Tie



DT
Double Entry Tie



TL2 and TR2
Tire Rack Cleats
(left and right hand)

Single Entry

Starter Units

1. Secure rivet heads of side supports into slots of uprights at measurements shown.
2. Lock in tire beams at measurements shown.
3. Use a mallet to secure installation.
4. Lock wall ties into rear upright posts and secure to wall using wall anchors (not provided). See chart below for quantities of wall ties.

Add-On Units

1. Assemble one side the same as a starter unit.
2. Lock a cleat next to each tire beam on the uprights of Starter Unit.
3. Lock tire beams of assembled add-on units to cleats.
4. Lock wall ties into rear upright posts and secure to wall using wall anchors (not provided). See chart below for quantities of wall ties.

Double Entry

Starter Units

1. Secure rivet heads of side supports into slots of uprights at measurements shown.
2. Lock in tire beams at measurements shown.
3. Add double entry ties to join the two units. See below for quantities.
4. Use a mallet to secure installation.

Add-On Units

1. Assemble one side the same as a starter unit.
2. Lock a cleat next to each tire beam on the uprights of Starter Unit.
3. Lock tire beams of assembled add-on units to cleats.

DT per Post Location

2 tier	1
3 tier	2
4 tier	2
5 tier	3
6 tier	3

