**Counting Scales** 

# **Counting Scales**

# **NEW** Digi® DC-782 Series

## **Portable Counting Scales**



## STANDARD FEATURES

- Liquid Crystal Display (LCD) with yellow backlight
- RS-232 output to PC
- 10 preset keys for product ID
- 25 item memory
- Internal resolution of 1/500,000
- Buzzer low, ok, high

## **SPECIFICATIONS**

#### **INTERNAL RESOLUTION:**

1/500,000

#### **WEIGHT DISPLAY RESOLUTION:**

1/7500 (1/6000)

#### DISPLAY:

Liquid Crystal Display (LCD) with backlight Weight: Five-digit Unit Weight: Five-digits Quantity: Six-digit

#### **POWER SOURCE:**

AC power supply or optional rechargeable battery

#### **NUMBER OF SCALE CHANNEL:**

One local scale

#### **MEMORY ITEMS:**

25

#### RS-232:

9 Pin to PC

#### **OPTIONAL BATTERY:**

Charge time: 12-14 hours Battery life: 300 hours (no backlight)

#### **OPERATING TEMPERATURE:**

14°F to 104°F (-10°C to 40°C)

#### **DIMENSIONS:**

Overall: 335.7 W x 349.7 D x 123.5 m H (8526.8 W x 8882.4 L x 3136.9 in H)

#### **ESTIMATED SHIPPING WEIGHT:**

5 kg

#### **PLATTER SIZE:**

300 x 225 mm (12 x 8.9 in)

#### **WARRANTY:**

Two-year limited warranty

## Digi® DC-688 Series

## Portable Counting Scales



#### STANDARD FEATURES

- Extra-wide stainless steel platter
- Three large numeric Liquid Crystal Displays (LCD) for weight, unit weight and quantity
- Six preset unit weight recall memory keys
- Count accumulation and subtraction function
- Negative sampling and counting (count out of a full container)
- Numeric keyboard
- Push-button or keyboard tare entry
- Net/gross weight display switching
- Internal buzzer
- 115VAC power
- Battery\*- saving auto power-off function (selectable settings: 3 minutes, 10 minutes, 30 minutes, 1 hour, 3 hours, disabled)

### **SPECIFICATIONS**

#### **INTERNAL RESOLUTION:**

1/30,000

### **WEIGHT DISPLAY RESOLUTION:**

1/6000 (1/7500)

#### DISPLAY:

Liquid Crystal Display (LCD) Weight: Five-digit Unit Weight: Five digits Quantity: Six-digit

## POWER:

115VAC

9V provided by six "D" cell batteries (500 continuous hours with standard "D" cell batteries, 1,000 hours with "D" cell alkaline batteries)

\* Batteries not included

## POWER CONSUMPTION:

1.5W

## **FREQUENCY:** 50 or 60 Hz

50 or 60 Hz

## OPERATING TEMPERATURE:

14°F to 104°F (-10°C to 40°C)

## **DIMENSIONS:**

Overall: 14.44 in L x 13.5 in W x 4.68 in H (367 mm L x 343 mm W x 119 mm H)
Platter: 13 in L x 10 in W (330.2 mm L x 254 mm W)
Carrying case (inside):
15 in L x 17 in W x 7 in H (381 mm L x 431.8 mm W x 177.8 mm H)

## **ESTIMATED SHIPPING WEIGHT:**

15 lb (7 kg)

## WARRANTY:

Two-year limited warranty





<sup>\*</sup> Batteries not included

<sup>\*</sup> Batteries not included