

MODEL 612612 TOP OF GROUND DOCK LIFT

2 Year Parts & Labor/10 Year Structural Warranty

These are Instant Docks that simply require lagging into position and plugging into a power receptacle and they are ready to go to work. No pit work is required.

ISO 9001:2015 Certified





Capacity: 12,000 lbs.

Axle Capacity Ends: 9,600 lbs.

Platform Size: 6 x 12 ft.

Overall Size w/Ramp: 88 x 189 in.

Lowered Height: 6 in.

Bridge Size: 18 x 60 in.

Ramp Size: 42 x 54 in.

7.5 HP Motor

Approx. 11 FPM

52" Travel



SPECIAL FEATURES & BENEFITS

- All models are equipped with a hinged bridge equipped with a pull back chain.
- All models have an approach ramp.
- ▶ All of the electrical controllers are Underwriters Laboratories approved assemblies.

Shipping Weight: 5,365 lbs.

- Each unit is washed with phosphoric acid, fully primed and then finished with baked enamel.
- All cylinders are machine grade with clear plastic return lines.
- All pressure hoses are double wire braid with JIC fittings.
- ▶ These units conform to all applicable ANSI codes.

FEATURE DETAILS




► Power Unit w/Controller



► UL Listed Control
Panel



► Double Wire Braid Hose



Combination Wheel Chock/Ramp

