82602620 1 OF 1

NOTES:

- 1. ALL PIVOT POINTS ARE EQUIPPED WITH LIFETIME LUBRICATED, HIGH IMPACT BEARINGS.
- 2. 2000 PSI MAXIMUM OPERATING PRESSURE.
- 3. LIFT TO BE PAINTED AQ STANDARD ENAMEL.
- 4. MEETS OR EXCEEDS ANSI MH29.1 STANDARD FOR INDUSTRIAL SCISSOR LIFTS.

THIS PROPOSAL DRAWING IS GENERIC BY DESIGN AND IS FOR REFERENCE ONLY. PLEASE CONTACT AUTOQUIP FOR JOB SPECIFIC APPROVAL DRAWINGS.

MODEL NO:	
MAX. CAPACITY:	
LOWERED HEIGHT:	
TRAVEL:	
RAISED HEIGHT:	

POWER UNIT, CONTROLS, AND ACCESSORIES PER QUOTATION.

-PLATFORM -LENGTH -PLATFORM: **WIDTH SMOOTH STEEL BEVELED TOE GUARDS** CAPTURED ROLLERS STRUCTURAL CHANNELS ON (4) SIDES WITH IN PLATFORM AND BLACK AND YELLOW **USED IN PLATFORM AND BASE FRAME BASE FRAMES** STRIPED TAPE **SELF-ALIGNING** TRAVEL CYLINDER(S) WITH CHROME PLATED ROD(S) AND -PLATFORM IN VELOCITY FUSÉ(S) LOWERED Ø3" PVC WITH MAINTENANCE-**POSITION** LONG RADIUS **DEVICES SWEEP ELBOWS** (4) \emptyset 9/16" HOLES FOR LAGGING LIFT SECURELY TO FLOOR (BY OTHERS) PIT DEPTH -DRAIN BASE (IF REQUIRED) BASE LENGTH 1/2" FOR **WIDTH SHIMMING** PIT LENGTH PIT WIDTH (PLATFORM LENGTH + 2) (PLATFORM WIDTH + 2

COMPACT - PIT MOUNTED

(NOT TO SCALE) PROPOSAL DRAWING QUOTE NO. 82602620

2012 COPYRIGHT RESERVED AUTOQUIP CORPORATION

American Lifts

BY AUTOQUIP CORP. 1058 W. INDUSTRIAL AVE. GUTHRIE, OK 73044-1058 888-811-9876 WWW.AUTOQUIP.COM