

# Fast Acting Vinyl Doors for Extreme Conditions!



# **High Speed**

Up to 28" per Second

# **Low Maintenance**

No Cables, Wheels, Springs, or Sewn Construction

# Wind Load Rated

45mph Wind Load\*

# **Durable**

Welded Seams & Fiberglass Windbars

# Reliable

Auto Reset Reverse Safety Feature

### **Extruded PVC Side Seals**

· Ensures a tight seal along vertical edges

### **Custom Fiberglass Windbars**

· Bend if loaded, won't break or kink

# **Custom Extruded Aluminum Side Beams**

• 2" deep sleek design

### **Slanted Upper Box**

· Slanted upper box allows for water run off

### **Auto Reset**

· Automatically resets after impact or blow out

### **Reverse Safety Feature**

• Door automatically reverses if beam photo eye is broken.





**Extruded PVC Side Seals** 



**Extruded Aluminum Side Beams** 



**Welded Seams** 



**Easily Exchangeable Panels** 

\*Wind Load tested on a 10' x 12' solid vinyl Roll-Up Door per ANSI/DASMA 108-2002

# **Operation**



### 2800 Series

- · 28" per second High Speed External Operator
- Completely Water & **Dust Proof**
- 24/40\*/70† Cycles per hour
- 110 Volt Motor
- Direct Quill Drive to Door
- Sealed Oil Bath Right **Angle Drive**
- Manual Crank Overide in Case of Power Failure

\*With high duty cycle upgrade twith high duty cycle and fan kit upgrade

# Mounting


### **Face Mount**

Mount outside to the Face of the building


### **Projection Mount**

Mount inside the building beyond the existing security door.

- Custom aluminum standoff brackets and corner gussets used to extend the door from the wall past the existing door.
- Vinyl filler panels included to fill the space between the wall and the door.



**Face Mount** 



**Projection Mount** 

# **Control Options**





(Standard)







Remote Control

# **Material & Sizes**

## Goff's G-2 Doors Come in Custom Sizes up to 16' x 16'

- Welded Seam Construction
- Easily Replaceable Panels
- 18 oz Vinyl & 40 Mil Clear PVC

### 18 oz Vinyl Color Options



# **Upgrade**

### High Wind Load Upgrade

For high wind areas upgrade to a higher wind load rated door.

Warranty: Goff's Enterprises, Inc warrants all Doors Systems for 3-years – limited warranty on materials and workmanship. Warranty excludes electric motor and spring-assist roll-up mechanism; warranty on these items is 1 year. Goff's reserves the right to repair or replace warranty items at its discretion.





**Distributed By** 

Goff's Enterprises, Inc., 1228 Hickory Street, Pewaukee, WI 53072 E-mail: sales@goffscw.com • www.goffscurtainwalls.com Phone: (262) 691-4998 • 800-234-0337; Fax (262) 691-3255 • 800-959-0170