


FX200/226

Heavy-Duty Skatewheel Conveyor

A proven performer for trailer loading and unloading. Ideally suited for packaging, shipping, and flexible assembly lines. Order optional leg connect brackets to lock units together.

- Structural Steel Support
- 1 1/4 in. Aluminum Side Plates



Model Number	Width	Compacted to Expanded	Conveyor Height	Leg Sets Per Unit	Wheels Per Axle	Unit Weight
FX200-18-12-ST-5	18 in.	3 ft. to 12 ft.	28 1/2" to 41 1/2"	4	7	215 lbs.
FX200-18-24-ST-5	18 in.	6 ft. to 24 ft.	28 1/2" to 41 1/2"	7	7	429 lbs.
FX200-24-12-ST-5	24 in.	3 ft. to 12 ft.	28 1/2" to 41 1/2"	4	9	252 lbs.
FX200-24-24-ST-5	24 in.	6 ft. to 24 ft.	28 1/2" to 41 1/2"	7	9	504 lbs.

FX200/226

Standard Specifications

WIDTHS – 18 in. and 24 in.

FRAME – Flexible and extendible.

LENGTH – 12 ft. and 24 ft.

EXPANSION RATIO – 4:1.

FLOOR SUPPORTS – Adjustable type 28 1/2 in. to 41 1/2 in.

WHEELS – 1.9 in. dia. with 1/4 in. bore.

PACKAGE STOP – Folds down when not in use.

CASTERS – Swivel casters with locking brake.

CAPACITY – 200 lbs. capacity per linear foot.

Optional Equipment

LEG CONNECT BRACKETS – Connecting two or more conveyors.



Leg Connect Brackets