

# PORTABLE CASTERED SUPPORT

Support Width				Height to Top of Conveyor	Weight (Lbs.)
12"	15"	18"	24"		
PCS-12-28	PCS-15-28	PCS-18-28	PCS-24-28	18"-28"	53
PCS-12-40	PCS-15-40	PCS-18-40	PCS-24-40	24"-40"	55
PCS-12-52	PCS-15-52	PCS-18-52	PCS-24-52	30"-52"	57
PCS-12-72	PCS-15-72	PCS-18-72	PCS-24-72	40"-72"	62

Portable Castered Support allows straight sections of gravity skatewheel or 1 3/8 in. dia. roller conveyor to be easily moved.

**NOTE:** Supplied with 3 in. dia. Hard Rubber stem type brake caster. All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.



# PORTABLE CASTERED CURVE SUPPORT

Support Width				Height to Top of Conveyor	Weight (Lbs.)
12"	15"	18"	24"		
PCCS-12-28	PCCS-15-28	PCCS-18-28	PCCS-24-28	18"-28"	69
PCCS-12-40	PCCS-15-40	PCCS-18-40	PCCS-24-40	24"-40"	71
PCCS-12-52	PCCS-15-52	PCCS-18-52	PCCS-24-52	30"-52"	73
PCCS-12-72	PCCS-15-72	PCCS-18-72	PCCS-24-72	40"-72"	78

Portable Castered Curve Support allows curved sections of gravity skatewheel or 1 3/8 in. dia. roller curves to be easily moved. Floor locks can be supplied—optional, see Page 167.



**NOTE:** Supplied with 3 in. dia. Hard Rubber stem type brake caster. All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

# TRIPOD STAND

Adjustable Tripod Stands are used with straight or curved sections of gravity skatewheel and 1 3/8 in. dia. roller conveyor. Optional leg angles can be supplied to fasten stand to floor.

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

- 4 widths
- Portable applications
- Easily Adjusted

**CAPACITY DATA:**

350 lbs. with 180 in./lbs. of torque on locking screw. (No Shock Loading).

Model No.	Width	Height (Top of Roller/Wheel)		Weight (Lbs.)
		Min.	Max.	
TS-12-18	12"	12"	18"	5 1/2
TS-12-30		18"	30"	8 1/2
TS-12-40		24"	40"	10 1/2
TS-12-52		30"	52"	13 1/2
TS-12-72		40"	72"	19 1/2
TS-12-110		60"	110"	23 1/2
TS-15-18	15"	12"	18"	6
TS-15-30		18"	30"	9
TS-15-40		24"	40"	11
TS-15-52		30"	52"	14
TS-15-72		40"	72"	20
TS-15-110		60"	110"	24
TS-18-18	18"	12"	18"	6 1/2
TS-18-30		18"	30"	9 1/2
TS-18-40		24"	40"	11 1/2
TS-18-52		30"	52"	14 1/2
TS-18-72		40"	72"	20 1/2
TS-18-110		60"	110"	24 1/2
TS-24-18	24"	12"	18"	7
TS-24-30		18"	30"	10
TS-24-40		24"	40"	12
TS-24-52		30"	52"	15
TS-24-72		40"	72"	21
TS-24-110		60"	110"	25



# ROLLER STAND

Adjustable Roller Stands are made of heavy gauge pipe with a 1.9 galvanized, ball bearing roller mounted on top. They are used for feeding work to a punch press, saw, drill press, brake press, or anywhere some extra support is required.

- 3 widths
- Portable applications
- Easily Adjusted

MODEL NO.	WIDTH BR	HEIGHT		Weight (Lbs.)
		MIN.	MAX	
ARS-13-18	13"	12 3/8"	18"	9
ARS-13-30		18 3/8"	30"	12
ARS-13-40		24 3/8"	40"	14
ARS-17-18	17"	12 3/8"	18"	10
ARS-17-30		18 3/8"	30"	13
ARS-17-40		24 3/8"	40"	15
ARS-21-18	21"	12 3/8"	18"	12
ARS-21-30		18 3/8"	30"	15
ARS-21-40		24 3/8"	40"	17

All weights in catalog are conveyor weights only. Accessories, crating, etc., are not included.

