
# **EDGE GUARDS**

# Knuffi® Model B

- A 1.57" (40 mm)
- **B** 1.57" (40 mm)
- C 0.31" (8 mm)






Available Colors: Black, Black/Yellow, Black/Fluorescent, Black/Photoluminescent, Red/White. White Pressure fit only. No adhesive.

### Knuffi® Model B+

- A 1.97" (50 mm)
- B 1.97" (50 mm)
- C 0.47" (12 mm)






Available Colors: Black, Black/Yellow Pressure fit only. No adhesive.

## Knuffi® Model BB


- A 1.57" (40 mm)
- B 1.42" (36 mm)
- C 0.31" (8 mm)
- D 0.75" (19 mm)





# Knuffi® Model G


- A 1.02" (26 mm)
- **B** 1.18" (30 mm)
- C 0.31" (8 mm)
- D 0.75" (19 mm)



Available Colors: Black, Black/Yellow, Red/White, White

#### Knuffi<sup>®</sup> W

- A 0.55" (14mm)
- B 1.02" (26mm
- C 0.75" (19mm)
- D 0.28" (7mm)
- **E** 0.039" (1mm)



Knuffi® W: Sharp edges no larger pose a threat with Knuffi®'s W Profile. It will easily flex to the thinnest of edges, right down to 0.039" (1mm).

# Knuffi<sup>®</sup> Sign



### **WARNING AND PROTECTIVE BUMPER GUARDS**





### **TECHNICAL DATA**

Profile Body: Recyclable polyurethane foam.

Surface: Polyurethane foam colored by reverse printing and foamed in place so no paint appears on the outside.

Temperature Range: -40°F to +212°F (-40°C to 100°C)

Fire Classification: DIN EN 13501-1 / Class E.

Colors:













Lengths: Most Black/Yellow adhesive-fastened models are available in 3' 3-1/4" (1m), 16' 4-3/4" (5m) and up to 164' 0" (50m) lengths. Other colors and installation styles may not be available in all sizes. Please consult Ideal Warehouse Innovations Inc. for more details.

5-year warranty for elasticity and color-fastness. Knuffi® must be fastened according to the installation recommendations. Exclusions include adhesive power and UV resistance.

Surface, pipe and corner guards are also available.

