Storefront Gates The Original Galvanized Steel Gate







Each Gate is Custom Manufactured to Each Customer's Application

- Protect Property and Merchandise
- Prevent Unauthorized Access
- Guard Against Vandalism
- Exceptional Quality Security, Custom Built in 7-14 Business Days
- Maintenance-free Galvanized Steel Construction
- Custom Powder Coated Colors Available
- 100% Made in America



The Preferred Security Gates for Protecting Businesses Since 1962


Storefront Folding Gates: The Original Galvanized Steel Gate

Hybrid Storefront Gates


Designed with a continuous frame, utilizing vertical bars and traditional scissor style webbing, Hybrid Gates provide total coverage and maximum security. Available in single or pair, each gate is custom manufactured to protect openings of any size.



SINGLE GATES



Fixed Top & Fold-Away Bottom Track Max Width 16' | Max Height 12'



Fold-Away Top & Bottom Tracks Max Width 16' | Max Height 7'9"

Scissor Storefront Gates

Hybrid Gate Specs (Maximum-Duty)

Finish: Galvanized, Powder Coat Colors Available


Webbing: ¾" x ¾" 14-gauge Steel

Vertical Channel: 1¼" x 5%" 14-gauge C-channel


Trolley: 1" Steel Wheels

Top & Bottom Track: 1⁷/₈" x 1⁵/₁₆" 11-gauge U-channel

PAIR GATES




Fixed Top & Fold-Away Bottom Track Max Width 32' | Max Height 12'




Fold-Away Top & Bottom Tracks Max Width 16' | Max Height 7'9"

Locking Bar: 1⁷/₄" x 1⁵/₁₆" 11-gauge U-channel Hasp: ³/₁₆" Steel Welded to Frame* Rivets: ¹/₄" x 1¹/₂" Steel *Padlock not included, Cylinder Lock optional

Hinge Bar: $1\frac{1}{2}$ " x $1\frac{1}{8}$ " 12-gauge Angle Iron



Fixed Top & Fold-Away Bottom Track



Fold-Away Top & Bottom Tracks

Gates are designed to secure areas wider than 20' and can be used to protect openings spanning several hundred feet. Scissor Storefront Gates are engineered to be wall-mounted providing heavy-duty security. Use optional top and/or bottom tracks for extra heavy-duty security.



Scissor Gate Specs (Heavy-Duty & Extra Heavy Duty)

 Finish: Galvanized, Powder Coat Colors Available


 Webbing: %" x ¾" 14-gauge Steel

 Frame: 1½" x 1½" 12-Gauge Angle Iron


 Trolley: 2" Diameter Zinc Steel Wheels

TOP & BOTTOM TRACK OPTIONS

Mounting Bracket: 2½" x 7" L-bracket, Zinc Plated Hasp: ¾6" Steel Welded to Frame* Minimum Gate Height: 34" *Padlock not included, Cylinder Lock optional




SINGLE GATE: Fixed Top Track Unlimited Width | Max Height 12



PAIR GATE: Fixed Top Track Unlimited Width | Max Height 12'



FIXED BOTTOM TRACK - Single Gate Max Width 6' | Max Height 8'6"



FIXED BOTTOM TRACK - Pair Gate Max Width 12' | Max Height 8'6"