

Outdoor Safety Lockers—4-hour Fire-Rated **NEW**

Higher fire rating—provides proximity advantage over non-combustible and 2-hour locker models

- 3-hour fire-rated door—third party tested and labeled.
- Gravity air flow vents—UL Listed fire dampers with fusible links.
- Leakproof all welded sump.

Manufactured with fire-rated and weatherproof construction, each 4-hour locker has an FM-approved fire-rated wall and roof design and meets EPA 40 CFR, NFPA 30 and NFPA 1 regulations. Multiple layers of fire-resistant gypsum wall board are encased between exterior heavy gauge steel and interior galvanized sheet steel for maximum durability. A leakproof, all welded sump provides compliant secondary containment of hazardous liquids. Galvanized steel grate flooring removes easily for cleaning.

Gravity air flow vents include UL Listed fire dampers and fusible links for maximum safety. Hydraulic door mechanism ensures door will automatically close. Forty-two inch (1.07-m) wide door comes with UL Listed keyed lockset for security. Additional safety features include static grounding connections, anchoring plates, and NFPA 704 diamond decal.

Designed to be placed within close proximity of existing structures and/or property set-backs, 4-hour fire-rated lockers provide a safe yet convenient storage solution. This proximity advantage over non-combustible and 2-hour lockers allows for the most efficient use, distribution and storage of your hazardous chemicals and drums of flammable liquids. NOTE: Please check with your local authority having jurisdiction for setback requirements and the correct wall/roof rating needed for your application.

Lockers are also available with FM-approved explosion relief panels that release at 20 psf to reduce the damage associated with a potential explosion.



Designed for close placement to existing structures, 4-hr fire-rated lockers provide a safe and convenient storage solution.



913060
6-drum capacity



Get answers to frequently asked questions . . .

Visit our website to learn more about choosing the proper locker design for your application, chemical storage guidelines, and more.

Global Protection

Justrite products are available worldwide. For pricing and availability, simply contact the authorized distributor nearest you.



55-Gal. Drum Capacity	Sump Capacity Gallons/Liters	Dimensions W x D x H		Approv/Lstg Regulation	Standard		Explosion Relief	
		Exterior*	Interior		Model No	Ship Wt lb/kg	Model No	Ship Wt lb/kg
2	75/284	71 in x 42 in x 75 in 1803 mm x 1067 mm x 1905 mm	50.5 in x 26.5 in x 52.5 in 1283 mm x 673 mm x 1334 mm	FM,N,A,E	913020	2200/998	913021	2065/937
4	71/269	71 in x 66 in x 75 in 1803 mm x 1676 mm x 1905 mm	50.5 in x 50.5 in x 59 in 1283 mm x 1283 mm x 1499 mm		913040	3036/1377	913041	2901/1316
6	105/397	95 in x 66 in x 97 in 2413 mm x 1676 mm x 2464 mm	74.5 in x 50.5 in x 81 in 1892 mm x 1283 mm x 2057 mm		913060	4330/1964	913061	4195/1903
9	155/587	95 in x 90 in x 97 in 2413 mm x 2286 mm x 2464 mm	74.5 in x 74.5 in x 81 in 1892 mm x 1892 mm x 2057 mm		913090	5467/2480	913091	5270/2390
12	205/776	88 in x 119 in x 97 in 2235 mm x 3023 mm x 2464 mm	74.5 in x 98.5 in x 81 in 1892 mm x 2502 mm x 2057 mm		913120	6468/2934	913121	6198/2811
16	272/1030	119 in x 114 in x 97 in 3023 mm x 2896 mm x 2464 mm	98.5 in x 98.5 in x 81 in 2502 mm x 2502 mm x 2057 mm		913160	7740/3511	913161	7475/3391

Note: Door height on 2- and 4-drum models is 51-in (1.30-m) high and 80-in (2.03-m) high on 6- through 16-drum models. *Dimensions include mounting plates and door hardware.

In most instances, locker sizes 2- through 6-drum are available to ship via a closed container truck, which can potentially reduce freight costs as compared to flat bed shipping alternatives.