



It's a Lantech!

Ideal for Very Light, Very Heavy or Very Unstable Loads

- Load Doesn't Rotate.
- No Weight Limitations.
- Precise Application of Wrap Force.
- Locks Load to Pallet with Film Cable.
- No Scheduled Preventative Maintenance.





S-300

Boost your machine's performance with these patented features:

Auto Film Cut-off

Save 30 seconds of labor per load!

Automatically punctures film so it cuts off at the corner of the load.



30" Film Delivery System 15 RPM Wrap Arm Speed 110" Wrap Height Cold Package **Conveyor Packages Extended Warranty** Freezer Package Lexan Plastic Cover Netting Film Delivery System One Way Wrap Pre-stretch Gears 100-300% Seismic Protection Package Static Collection Brush **Top Sheet Wrap** Two-Speed Roll Carriage and Wrap Arm Wrap Cycle Pause . . . and more!

Increase Productivity Even More. Upgrade to a S-300XT Stretch Wrapper.

Work Smarter . . . Keep your driver on the fork truck!


Patented XT Cut and Clamp[®] automatically captures the stretch film and cuts it at the end of the wrap cycle.

Save two minutes of fork truck driver labor per load.

S-300 Specifications

PERFORMANCE CRITERIA Production Speed Maximum Load Diagonal Maximum Load Height	25-35 loads per hour 76" 80"
FILM DELIVERY SYSTEM	200% Standard
Power-Roller Stretch System	(100%-300% available)
Wrapping Force	Electronically controlled
Film Capacity	10" Roll Diameter, 20" Film Web Width
E-Z Thread Roll Carriage	Standard
Pallet Grip®	Standard
MACHINE SHIPPING WEIGHT	157"W x 172"L x 121"H
■ Machine Size	3200 lbs.
■ Shipping Weight	(including skid - approximate)
ELECTRICAL REQUIREMENTS Machine Voltage Microcontroller UL-Approved NEMA 12/enclosure	115V, 20 Amp Standard Standard
SERVICE SUPPORT	24 hrs/7 days a week
PHONE NUMBER	800-866-0322

Specifications subject to change without notice. Lantech systems and sub-systems are protected by U.S. and foreign patents. Additional U.S. and foreign patents pending. © Lantech







S-300 Rev. 03/28/16 Page 2 of 2 Part #31024958