

U-BOAT INDUSTRIAL USE



U-BOAT



- Engineered for durability, longevity and extreme use
- Bottom cross brace rests on deck to provide load containment
- Handle extends through deck for improved retention in the deck
- Center tilt allows easy navigation over thresholds and bumps
- 360-degree maneuverability in aisles and most coolers
- High efficiency tire treads for easy rolling and reduction of push-and-pull effort by drivers during delivery

P/N BDHA162

Shown with 6" casters.

Handle Benefits



P/N 306150

- Modular construction offers service parts vs. total handle replacement
- Hardware secured with automotive grade thread locking bolts for superior performance
- Ergonomic oval handle shaped for comfort
- Industrial grade engineered for controlled handling
- Grooved surface for positive grip

SPECIFICATIONS				
Deck	18" wide x 60" long			
Weight	80 lbs.			
Capacity	1,500 lbs. route delivery 1,800 lbs. in-store use			
Handles	48" high			
Casters	6" or 8"x 2"			



Robotically welded five-box aluminum construction optimized for over-the-road payload.

Accessories







Containment curtain securely holds the highest payload per U-Boat.



The quick pick adapter option allows users to utilize walkie-riders to speed order picking. Two U-Boats fit securely on a walkie-rider allowing warehouse order picking from both sides. U-Boat must have 6" TPR casters. Incompatible with foot brake option.







Options



P/N	WT.(LBS.)
349530 6" Casters	8.0
349500 8" Casters	8.0

The foot brake helps hold the U-Boat in place on inclines or when loading products.



P/N	D"	W"	WT.(LBS.)
130066 Swivel	6	2	5.0
130067 Rigid	6	2	4.0
130079 Swivel	8	2	6.0
130029 Rigid	8	2	5.0

 $\label{thm:continuous} \mbox{Heavy duty thermoplastic rubber casters.}$