



SAFESTOP GUARDRAIL

INNOVATIVE GUARDRAILS
KEEP YOUR PEOPLE SAFE



Strong uprights and flexible rails
provide ultimate stopping power

THE MCCUE DIFFERENCE

HI, WE'RE MCCUE & WE MAKE SAFETY EASY!

Our innovative, impact-tested barriers safely stop fast-moving material handling vehicles — protecting your people and your facility. With engineered materials that work together, we're revolutionizing safety barrier innovation with these three principles:



SAFER IMPACTS

Strong, floor-mounted rail designed to bring heavy trucks to a stop.



SHOCK ABSORPTION

Absorbs impacts — with limited deflection — to keep your people safe.




EASY INSTALL

Simple install with standard hardware and tools.

**KEEP YOUR OPERATIONS SAFE AND YOUR WORKFORCE SAFER
WITH THE WORLD'S MOST ADVANCED SAFETY BARRIERS**




EASY-TO-CONFIGURE:
Modular posts and rails allow for endless configurations.



SAFER IMPACTS:
Proprietary rail connection provides unparalleled impact absorbency.



STOPPING POWER:
Industry-leading upright strength from shock-absorbing post technology.



SAFESTOP GUARDRAIL

Meet **Safestop GuardRail**, a strong plate-mounted barrier that safely stops moving material handling vehicles. Engineered to safely absorb impacts —with flexible polymer rails — to protect your people, workspace, and bottom line.

HOW IT WORKS

GuardRail is packed full of innovative technology to safely stop heavy machinery. Upon impact, its reinforced uprights offer strength while its shock-absorbing rails flex to dissipate impact energy — keeping your operators, forklifts, and facility safe.



* PATENTS PENDING



IMPACT TESTING

Rigorous product testing at the highest standard.







$$\frac{1}{2} \text{ MASS } \times \text{ VELOCITY}^2 = \text{ ENERGY}$$

90°	21,389 ft-lbs	29,000 J
-----	---------------	----------

45°	30,254 ft-lbs	41,018 J
-----	---------------	----------

30°	42,779 ft-lbs	58,000 J
-----	---------------	----------


WHAT DOES 21,389 FT LBS (29,000 J) MEAN TO YOU?



MATERIAL PROPERTIES


BARRIER DEFLECTION:

Flexible rails for maximum energy absorption.



Anchor Specifications:

A shock-absorbing anchor system protects both the anchors and the floor.



	Working Temperatures	32°F-130°F (0°C-54°C)
	Toxicity	Not Hazardous




	Flammability	Does Not Easily Ignite
	REACH / TSCA / DSL	Compliant

* PATENTS PENDING

SAFESTOP **GUARDRAIL**

SafeStop GuardRail

Hardware included.



* PATENTS PENDING