



# Mezzanine Safeti-Gates, Inc.

An **OPEN** and **SHUT** Case for Plant Safety

## SAFETY GATE POWER SPECIFICATIONS

### **Power Option:**

Most of the pallet drop safety gates manufactured by Mezzanine Safeti-Gates, Inc. can be power operated. Optional power unit includes 110 volt, ½ horsepower, 1,000 RPM, commercial motor that is attached to safety gate system with included powder-coated steel brackets. Power unit includes one (1) three (3) button switch for open, close and stop that is positioned on or adjacent to the unit. An additional push-button station can be added and positioned on the ground level to be accessed by the fork lift driver. Power motor also includes Radio Frequency receiver so wireless push-button controls can be utilized to operate the safety gate remotely, such as on the lift truck. Power motor includes a clutch operation that will engage if the gate is obstructed when closing. Limit switches on the unit can vary the sensitivity of this clutch operation. Photo eyes are also included (and must be connected for unit to operate), and typically are installed on the rear-side posts. If an object or person are in the area and interrupting the beam for the photo eyes then the gates will not operate, creating an extremely safe environment.

An **OPEN** and **SHUT** Case for Plant Mezzanine Safety

Distributed by



888-877-3861

[www.cisco-eagle.com](http://www.cisco-eagle.com)