Enduro Trekking B is the first fast industrial flexible door designed for exterior openings up to 36 x 36 ft and its mechanism can be accessed from the front.

It can be fitted with a single layer curtain, or double layer curtain for increased insulation.


Also available in the same product line: Enduro Trekking A (above access), Trekking C (access from below), Enduro Puissance for strong winds, and Enduro Forum for interior, including corridors.

NERGECO

Over 25 years' experience in productivity doors for your industry, your process, your site

Installation

The independent structure is fitted in the opening, inside or outside of the area to be insulated..




Operation


- Opening: "just in time", manual or automatic with all kinds of activator, with a speed up to 32 in/s based on curtain dimension.
- Closing: "fast", manual or automatic with an adjustable timer, at a speed up to 32 in/s based on dimensions.


Insulation

- Closed door: the horizontal reinforcements keep the edges of the curtain in contact with the structure, offering uniform wind resistance (2).
- At each cycle: the free[®], multiflexible[®] and reactive[®] soft bottom edge limits the volume of air entering through the opening with "just in time[®]" opening and closes twice faster than classic curtains (4).



- Power-free opening: counterbalance weight.
- Motor unit: housed in the structure, power from 1.5 to 7.5 hp based on dimension.
- Power supply: 208/230/460/575 V 3 phase plus ground, 60 Hz, upstream circuit breaker protection.











Savings

- With no folding bars in the vertical guides and no rigid bottom bar (1), the closing edge is flexible with over 15 inches in height and over the complete width of the opening, therefore decreasing incidents and maintenance costs.
- The opening time is cut by half, and so is the cost of the energy consumed for the heating or air conditionning.
- Durability and reliability guaranteed with smooth direct drive.

