Copyright NERGECO 2010 - 19/01/

STARS Forum Business Version

The **Star 5 Forum Business** combines:

A flexible curtain held by horizontal flexible stiffeners in vertical guides.

A free®, multi flexible® soft bottom edge on 13 inches in height and the whole width of the opening.

Structure and mechanism in high performance, smooth, non corrosive multi-composite material


Dimensions up to 14 x 15 ft.

For more options, see Star 5 Forum in Privilege or Emergency Exit versions.

NERGECO

## Installation

The independent structure is fitted in the opening, inside or outside of the area to be insulated.



## **Operation**


- Opening: "just in time", manual or automatic with all kinds of activator, at a speed up to 48 in/s based on curtain dimension.
- Closing: "fast", manual or automatic with an adjustable timer, at a speed up to 48 in/s.
- ratchet handle, crank handle or counterbalance weight.

## Insulation

- Closed door: : the flexible curtain guarantees a leakage area inferior to 1.61 sq ft under a pressure up to 2.7 inWC (2).
- In intensive use: : it limits the air exchange thanks to its free®, multiflexible® soft bottom edge which allows "just in time" opening and safely closes twice faster than classic doors.



- Motor unit: fitted on the left or right side Power I hp.
- ower supply: 208/230/460/575 V, 3 phase plus ground, 60 Hz, upstream circuit breaker protection.











## **Savings**

- With no bottom bar nor captured in the guides (1), the free<sup>®</sup> multiflexible<sup>®</sup> soft bottom edge slides over the obstacle with no subsequent damage (3).
- The reactive® curtain automatically re-opens as soon as a vertical or horizontal deformation (4) is detected.
- The high-resistance multi-composite mechanism is corrosion resistant and offers increased durability and reliability.

· Spare parts readily available from stock.



Comparison base 100 to 316L stainless steel



tel. 888-872-0424 fax 513-554-3101 www.nergeco.com