

14"

HIGH VELOCITY FAN galvanized



YM -Yoke Mount (standard)

mounting options:



PS - Pedestal Stroller



CW - Column Wall



PB - Pedestal Base

Shipping Weights:

80 lbs/ 36 kg

64 lbs/ 29 kg

56 lbs/ 23 kg

SIZE	CFM	HP	FAN DIMENSIONS			DISTANCE AIR THROW	SHIPPING WEIGHT
			W	D	I.D.		
14"	2600	1/4	20"	16"	14.625"	60' / 18 m	42 lbs/ 19 kg

Propeller: 14" Diameter, 3 Blade GalvAlum (37 Degree)
Fan Inlet/Outlet: Galvanized 16 Gauge Spun Steel
Finger Guards: Stainless Steel Spiral
RPM: 1725
Decibels: 66.5 @ 20'

Enclosure: TEAO Standard/ Washdown Available
Frame: 48
Ambient Temperature: 40C
Duty Cycle: Continuous
Power Cord (115V Only): 12' Length
Coverage: 1800 Sq.Ft. Max
Warranty: 2 Years

Voltage	Motor Amps	Running Amps
115V/ 208-230V*	2.8/ 1.4	2.8/ 1.4
208-230/ 460V	1.5-1.4/ .75	1.4/ .70
277V	1.1	1.1

* standard

14" High Velocity Fan Air Flow Pattern

