

The PowerStak Difference

Presto PowerStak[™] is a family of high performance, fully powered stackers that offer significant performance advantages over manual stackers without a significant price premium.

PowerStak Stackers provide instant flexibility and versatility. Whether used as a dedicated stacker, or as a combination stacker/ work positioner, or as a transporter, they provide significant improvements in worker productivity. An abundance of ergonomic features make PowerStak Stackers the safest, easiest to operate powered stackers available. Sleek, stylish design, low overall weight, and quiet operation allow them to fit nicely into a wide variety of work environments including: *warehouses, loading docks, light assembly work cells, retail sales floors and more.*

Seven PowerStak models are available to satisfy any requirement including servicing racks up to 12 feet high. Fork Over models can be used with open bottom pallets or skids and adjustable straddle units are available for use with any pallet style, even closed bottom.






Narrow mast and offset design provide workers a clear view with no blind spots.



Tight turning radius allows PowerStak to work in much narrower aisles than conventional forklift trucks.



Adjustable fork carriage allows forks to be repositioned to best accommodate loads (straddle only).



Auto-reversing "belly bump" switch protects against operator accidents while working in tight quarters.



Sealed, maintenance-free AGM batteries and heavy-duty built in charger with fuse protection.



Ergonomic handle with comfort-grip controls and switch redundancy for left- or right-hand operation.



Solid steel straddle legs provide rigidity and eliminate deflection even under maximum load conditions.



Turtle speed setting reduces drive speed by 50% for precise positioning or when working in tight quarters

Straddle Design 📻 📻 🖚

Model	PPS2200-62NAS	PPS2200-101AS	PPS2200-125AS	PPS2200-150AS	PPS3000-125AS
Lift Height	62"	101"	125"	150"	125″
Capacity	2,200 lbs.	2,200 lbs.	2,200 lbs.	2,200 lbs.	3000 lbs.
Load Center	24"	24"	24"	24"	24"
Forks (adjustable welded)	42"	42"	42"	42"	42"
Individual Fork Width	6"	6"	6"	6"	4" forged
Straddle I.D. (adjustable)	40" - 50"	40" - 50"	40" - 50"	40" - 50"	40.125" - 50"
Max. Overall Width (straddle legs)	48" - 58"	48" - 58"	48" - 58"	48" - 58"	48" - 58"
Overall Height (lowered/raised)	80" / 80"	73" / 122.5"	85" / 146.5"	99" / 172.75"	86" / 150"
Weight (without load)	1,050 lbs.	1,390 lbs.	1,445 lbs.	1,610 lbs.	2500 lbs.
Lifting Speed (without load)	4.8" / sec.	4.8" / sec.	4.8" / sec.	4.8" / sec.	5"/sec.
Turning Radius	54"	58"	58"	58"	67"
Drive Motor	750 Watt	750 Watt	750 Watt	750 Watt	1.5 KW
Battery (2)	12 volt 75 amp hr	12 volt 150 amp hr			

Adjustable width Straddle Legs on all units



Fork Over Design 📻 📻 🛶

Model	PPS2200-62NF0-21	PPS2200-62NF0-27	
Lift Height	62"	62"	
Capacity	2,200 lbs.	2,200 lbs.	
Load Center	24"	24"	
Fork Length	42"	42"	
Individual Fork Width	6"	6"	
Max. Distance Between Forks	9"	15"	
Max. Overall Width of Forks	21"	27"	-7
Overall Height	78"	78"	
Overall Width	32"	32"	
Weight (without load)	900 lbs.	900 lbs.	
Lifting Speed (without load)	4.8" / sec.	4.8" / sec.	
Turning Radius	53"	53"	
Drive Motor	750 Watt	750 Watt	1 7
Battery (2)	12 volt 75 amp hr	12 volt 75 amp hr	

Options

PowerStak units are available with these standard options. Other options may be available. Not all options shown are available for every PowerStak Model. Consult factory for details.

Load Backrests - to prevent loads from shifting when raised to full height Rubber Drive Wheel - for better traction on uneven surfaces Non-Marking Rubber Drive Wheel - to prevent scuffing/marking of floors Forged Forks - one piece construction for maximum strength and rigidity

PowerStak Counterbalance Stackers

Presto Counterbalance Stackers are ideal for die handling or machine feeding applications where straddle legs could get in the way. They can also be used for servicing rack or loading and unloading trucks. Unit comes standard with manual adjustable tilt mast.

Model	PPS1100-62-CB	
Lift Height	62"	
Capacity	1,100 lbs.	
Load Center	15"	
Fork Length	30"	
Individual Fork Width	4"	
Overall Height	86"	TETET
Overall Width	35"	
Lifting Speed (without load)	3.2" / sec.	a a a
Weight (without load)	2,205 lbs.	Works with any style
Battery (2)	12 volt 100 amp hr	pallet or skid, even closed bottom.









Counterweight Stackers

Manual Stackers



Straddle Stackers



Specialty Stackers

The PowerStak Warranty

Presto Lifts warrants the Power Stacker against defects on the mast, fork carriage, chains, pumps, DC motors, controllers, cylinders and wiring harnesses from faulty material and workmanship for a period of one (1) year from the date of invoice.

All wear items such as batteries, wheels, motor brushes, seals, bearings, hydraulic hoses, all switches, battery chargers and forks have a limited warranty against defects in faulty material and workmanship for a ninety (90) day period from the date of invoice and 30 day limited warranty on labor. Please note that prior authorization from Presto Lifts is required on all warranty work.



