

# WEIGHING SYSTEMS To be the best by every measure


www.ricelake.com

## **Summit** 3000 SERIES LOW PROFILE FLOOR SCALE

#### An Economical Choice Offering Exceptional Performance



The Summit® 3000 Series provides exceptional performance in light industrial and legal-for-trade applications. While value-priced, the Summit 3000 also employs a rugged design to deliver efficient installation and operation.



The convenient top-access junction box is housed in a durable ABS enclosure and is protected from fork trucks and other industrial abuse by the Summit 3000's diamond treadplate steel deck. The scale has fully adjustable, rigid polyurethane rubber feet to accommodate weighing on uneven surfaces.



The load cell cable exits the weldment towards the interior of the scale, allowing you the flexibility to route it out any side of the scale to the digital weight indicator. This also means the indicator load cell cable is at floor level—reducing the potential for damage.



### Floor Scale & Indicator Package

Add a 120/120 Plus indicator to the Summit 3000 for a total weighing solution. While value-priced, both deliver reliability and simple operation suitable for a range of light industrial applications.

#### **Standard Features**


- Four NTEP-certified alloy steel shear-beam load cells
- Top access junction box
- Steel diamond treadplate deck
- Four adjustable rigid polyurethane rubber feet, 3" (76.2 mm) diameter
- Signal-trim summing board housed in ABS enclosure
- One threaded eyebolt hole located in the center of the weldment for easy lifting
- 20 ft of EL147 load cell cable
- Conduit for additional load cell cable protection

#### **Options/Accessories**

- Floor anchor plates, mild steel (set of two)
- Four drilled deck holes for scale height adjustment

#### **Pit Frames**

For pit installations, frames are available with design drawings.



#### **Access Ramps**

For above ground applications, ramps are available for scale access convience.



#### **Specifications**

End Load Capacity: 100% full scale on 2,000 and 5,000 capacity

80% full scale on 10,000 capacity

**mV/V Output:** 1.50 – 1.87 mV/V nominal

Cable Length: 20 ft (6.1 m) of EL147g for connecting

to indicator

Warranty: Two-year limited warranty

Size (W x L x H)	Capacity
3' x 3' x 3.625"	.2,000 lb (1,000 kg)
4' x 4' x 3.625"	.2,000 lb (1,000 kg)
4' x 4' x 3.625"	.5,000 lb (2,500 kg)
4' x 4' x 3.625"	. 10,000 lb (5,000 kg)
4' x 5' x 3.625"	.5,000 lb (2,500 kg)
4' x 5' x 3.625"	. 10,000 lb (5,000 kg)
4' x 6' x 3.625"	.5,000 lb
4' x 6' x 3.625"	. 10,000 lb
5' x 5' x 3.625"	.5,000 lb (2,500 kg)
5' x 5' x 3.625"	. 10,000 lb (5,000 kg)

#### **Approvals**



Measurement Canada

Your Rice Lake Weighing Systems distributor is:

