# **Single-Depth On-Line Shelving**

Shelving specifically designed for assembly line production. With the shelves angled at 15°, workers can easily see and pick the parts they need, which new parts are supplied from the back. Bottom shelves can be inverted so that empty containers slide out of the way. On-Line offers a cost-efficient stock and storage solution for assembly line operations and is an effective way to utilize the valued space of most assembly line processes.

- Pre-assembled frames
- Starter, Add-on Principle
- Heavy duty, rigid construction
- Each shelf level supports up to 550 lbs
- Shelves are welded double box-style construction
- · Available in five widths and three depths
- Can be used with casters in 60" height
- Supplied with foot plates for anchoring units to the floor
- Frames are available in standard gray galvanized finish







Type S (Tilted)





ON-LINE SINGLE DEPTH WITH FIVE SHELF LEVE				
TH ODDED #	AU DEDTH ODDED #			

ITEM		20" DEPTI	l ORDER#		24" DEPTI	32" DEPTH ORDER #			
		WIDTH 39"	WIDTH 50.5"	WIDTH 36"	WIDTH 39"	WIDTH 48"	WIDTH 50.5"	WIDTH 39"	WIDTH 50.5"
HEIGHT 78.75"	Type G Starter	OLSU.2039G	OLSU.2050G	OLSU.2436G	OLSU.2439G	OLSU.2448G	OLSU.2450G	OLSU.3239G	OLSU.3250G
	Add-on Unit	OLAU.2039G	OLAU.2050G	OLAU.2436G	OLAU.2439G	OLAU.2448G	OLAU.2450G	OLAU.3239G	OLAU.3250G
	Extra Shelf	OLSK.2039G	OLSK.2050G	OLSK.2436G	OLSK.2439G	OLSK.2448G	OLSK.2450G	OLSK.3239G	OLSK.3250G
	Type S Starter	OLSU.2039S	OLSU.2050S	OLSU.2436S	OLSU.2439S	OLSU.2448S	OLSU.2450S	OLSU.3239S	OLSU.3250S
	Add-on Unit	OLAU.2039S	OLAU.2050S	OLAU.2436S	OLAU.2439S	OLAU.2448S	OLAU.2450S	OLAU.3239S	OLAU.3250S
	Extra Shelf	OLSK.2039S	OLSK.2050S	OLSK.2436S	OLSK.2439S	OLSK.2448S	OLSK.2450S	OLSK.3239S	OLSK.3250S









## **On-Line Shelving Assembly**

On-line Shelving, like all Schaefer Shelving, is simple, fast and easy to assemble—one unit takes about three minutes to set up. The simplicity of the design, which offers all the features of a highly engineered system, is a Schaefer trademark.

- On-Line Shelving is shipped with preassembled upright frames
- Single-depth units assemble in three minutes
- No tools are required for assembly
- Shelves are supported by beams which quickly connect to uprights
- Shelf levels adjust in 2" increments
- 500 lb Maximum Capacity per shelf level

ON-LINE FRAMES								
DEPTH 20" DEPTH 24" DEPTH 32" HEIGHT								
OLFR.2060GV2	OLFR.2460GV2	OLFR.3260GV2	60"					
OLFR.2079GV2	OLFR.2479GV2	OLFR.3279GV2	78.75"					





## **Double-Depth On-Line Shelving**

You can choose from either single-depth or double-depth units to fit your operation. On each unit, shelves can be tilted either toward the front and/or back. You also can combine straight and tilted shelves at the front and/or back.

- Improves assembly line productivity
- Tilted shelves allow material to flow toward working area
- User Friendly, 15° tilt angle makes parts easy to see and to pick
- Beams are made to withstand the most grueling impact loading
- Available in three widths
- · Available in four basic configurations
- Flexible enough to meet the needs of any operation
- Shelves adjust in 2" increments



Type GH Double-Depth Bay with a Combination of Straight and Tilted Shelves

#### ON-LINE DOUBLE DEPTH WITH FIVE SHELF LEVELS

	ITEM	40" DEPTH ORDER #			48" DEPTI		64" DEPTH ORDER #	
	ITEM	WIDTH 39"	WIDTH 50.5"	WIDTH 36"	WIDTH 39"	WIDTH 48"	WIDTH 48.5"	WIDTH 39"
	Type H Starter	OLSU.4039H	OLSU.4050H	OLSU.4836H	OLSU.4839H	OLSU.4848H	OLSU.2450H	OLSU.6439H
	Add-on Unit	OLAU.4039H	OLAU.4050H	OLAU.4836H	OLAU.4839H	OLAU.4848H	OLAU.2450H	OLAU.6439H
HEIGHT 78.75"	Extra Shelf	OLSK.4039H	OLSK.4050H	OLSK.4836H	OLSK.4839H	OLSK.4848H	OLSK.2450H	OLSK.6439H
HEIGHT 78.73	Type G Starter	OLSU.4039G	OLSU.4050G	OLSU.4836G	OLSU.4839G	OLSU.4848G	OLSU.2450G	OLSU.6439G
	Add-on Unit	OLAU.4039G	OLAU.4050G	OLAU.4836G	OLAU.4839G	OLAU.4848G	OLAU.2450G	OLAU.6439G
	Extra Shelf	OLSK.4039G	OLSK.4050G	OLSK.4836G	OLSK.4839G	OLSK.4848G	OLSK.2450G	OLSK.6439G
	Type Z Starter	OLSU.4039Z	OLSU.4050Z	OLSU.4836Z	OLSU.4839Z	OLSU.4848Z	OLSU.2450Z	OLSU.6439Z
	Add-on Unit	OLAU.4039Z	OLAU.4050Z	OLAU.4836Z	OLAU.4839Z	OLAU.4848Z	OLAU.2450Z	OLAU.6439Z
UEICUT 70 7E"	Extra Shelf	OLSK.4039Z	OLSK.4050Z	OLSK.4836Z	OLSK.4839Z	OLSK.4848Z	OLSK.2450Z	OLSK.6439Z
HEIGHT 78.75"	Type S Starter	OLSU.4039S	OLSU.4050S	OLSU.4836S	OLSU.4839S	OLSU.4848S	OLSU.2450S	OLSU.6439S
	Add-on Unit	OLAU.4039S	OLAU.4050S	OLAU.4836S	OLAU.4839S	OLAU.4848S	OLAU.2450S	OLAU.6439S
	Extra Shelf	OLSK.4039S	OLSK.4050S	OLSK.4836S	OLSK.4839S	OLSK.4848S	OLSK.2450S	OLSK.6439S

Note: For Overall Width of Starter, add 4 3/4 " to Shelf Width. For Overall Width of Add-on, add 2 3/8" to Shelf Width





Type G



Type Z


# **SSISCHAEFER**



### On-Line Double-Depth With Five Shelf Levels

### **Shelf Bracket**

- In double-depth units, used to support shelf levels at rear of forward shelf and front of rear shelf
- Adapter required for the Type SS units
- Securely locks front and rear bays together.




Shelf Bracket with Adapter

Note: For Overall Width of Starter, add 4 3/4 " to Shelf Width. For Overall Width of Add-on, add 2 3/8" to Shelf Width









## **On-Line Shelving Accessories**

A Work Table can be added to an On-Line shelving unit to provide additional space at an assembly station or in a workshop. For detailed repair work or assembly, a Workbench with drawers is available. When semi-open front containers are added, the On-Line unit with Workbench becomes a complete, compact work station where everything is within easy reach. For hanging tools, a perforated side panel available.

#### **On-Line Work Table**

- Attachable Work Table connects to the front beam and upright frames
- 16" deep
- Available in three widths

### **On-Line Cantilever Leg**

- Uses a staggered front leg which can be attached to any workbench
- Shown with Schaefer semi-open front containers



Cantilevered Leg Shown with Workbench (Workbench Must Be Ordered Separately)



ON-LINE SINGLE DEPTH CANTILEVER LEG WITH THREE SHELF LEVELS										
	ITEM	20" DEPTH ORDER #			24" DEPTI	32" DEPTH ORDER #				
	ITEM W	WIDTH 39"	WIDTH 50.5"	WIDTH 36"	WIDTH 39"	WIDTH 48"	WIDTH 50.5"	WIDTH 39"	WIDTH 50.5"	
	Type G Starter	OLCS.2039G	OLCS.2050G	OLCS.2436G	OLCS.2439G	OLCS.2448G	OLCS.2450G	OLCS.3239G	OLCS.3250G	
	Add-on Unit	OLCA.2039G	OLCA.2050G	OLCA.2436G	OLCA2439G	OLCA.2448G	OLCA.2450G	OLCA.3239G	OLCA.3250G	
HEIGHT 78.75"	Extra Shelf	OLSK.2039G	OLSK.2050G	OLSK.2436G	OLSK.2439G	OLSK.2448G	OLSK.2450G	OLSK.3239G	OLSK.3250G	
	Type S Starter	OLCS.2039S	OLCS.2050S	OLCS.2436S	OCLS.2439S	OLCS.2448S	OLCS.2450S	OLCS.3239S	OLCS.3250S	
	Add-on Unit	OLCS.2039S	OLCA.2050S	OLCA.2436S	OLCA.2439S	OLCA.2448S	OLCA.2450S	OLCA.3239S	OLCA.3250S	
	Extra Shelf	OLSK.2039S	OLSK.2050S	OLSK.2436S	OLSK.2439S	OLSK.2448S	OLSK.2450S	OLSK.3239S	OLSK.3250S	

ON-LINE CANTILEVER FRAMES								
DEPTH 20" DEPTH 24" DEPTH 32" HEIGHT								
OLCF.2060GV2	OLCF.2460GV2	OLCF.3260GV2	60"					
OLCF.2079GV2	OLCF.2479GV2	OLCF.3279GV2	78.75"					

## **55ISCHAEFER**



Other Configurations Are Available. Contact Project Services

#### **On-Line Accessories**

ON-LINE ACCESSORIES						
WIDTH ORDER #						
End Cap	OLCAP					
Casterset	OLCS					



**End Caps** 

### **Perforated Side Panel**

- Encloses side of units
- Steel Mesh
- Closes off the end of a row of On-Line Shelving units
- Creates pegboard-type surface for hanging items

### **End Caps**

- Recommended for 60" units
- Additional safety feature
- Prevents injury from edges when reaching to top level and above

#### **Casters**

- Unit with casters moves parts to the places they're needed
- Used only with single-depth unit, 60" high
- One caster set includes two fixed wheels and two swivel wheels with foot brakes



Casters Are Available for Single –Depth Units, 60" High

ON-LINE MOBILE SINGLE DEPTH WITH FOUR SHELF LEVELS										
	ITEM	20" DEPTI	H ORDER #		24" DEPTI	32" DEPTH ORDER #				
HEIGHT 67.5"		WIDTH 39"	WIDTH 50.5"	WIDTH 36"	WIDTH 39"	WIDTH 48"	WIDTH 50.5"	WIDTH 39"	WIDTH 50.5"	
	Type G Starter	OLMU.2039G	OLMU.2050G	OLMU.2436G	OLMU.2439G	OLMU.2448G	OLMU.2450G	OLMU.3239G	OLMU.3250G	
	Extra G Shelf	OLSK.2039G	OLSK.2050G	OLSK.2436G	OLSK.2439G	OLSK.2448G	OLSK.2450G	OLMU.3239G	OLMU.3250G	
	Type S Starter	OLMU.2039S	OLMU.2050S	OLMU.2436S	OCMU.2439S	OLMU.2448S	OLMU.2450S	OLMU.3239S	OLMU.3250S	
	Extra Shelf	OLSK.2039S	OLSK.2050S	OLSK.2436S	OLSK.2439S	OLSK.2448S	OLSK.2450S	OLMU.3239S	OLMU.3250S	