Specifications

Part# 1330-1335

Ultra-Utility Tray® Flexible Models

Advantage MVP 18 is an 18 oz. coated formula known for strength and consistency. This sturdy material is well equipped to handle adverse weather conditions and

withstand great physical stress. In contrast to its tremendous strength, the soft hand and aesthetic smooth matte finish give it a quality feel and appearance.

Neight 18.5 oz./yd² 627 g/m2 FS 5040 / ASTM D3776 Widths				
Widths up to 126" up to 320 cm - Construction 18 x 17/1" 7 x 7/cm by 1100 x 1430 - Grab Tensile 375 x 375 lbs./1" 1668 x 1668 N/2.5 cm FS 5100 / ASTM D5034 Tongue Tear 100 x 100 lbs./1" 445 x 445 N/2.5 cm FS 5134 / ASTM D2261 Adhesion 26 lbs./2" 116 N/5 cm FS 5970 / ASTM D751 Cold Crack -30° F -34° C FS 5874 / ASTM D2136 Treatments Anti-Mildew, UV Pigments Fire Retardant Self Extinguishing Finish Matte		English	Metric	Testing Method
Construction 18 x 17/1" 7 x 7/cm by 1100 x 1430 - Grab Tensile 375 x 375 lbs./1" 1668 x 1668 N/2.5 cm FS 5100 / ASTM D5034 Tongue Tear 100 x 100 lbs./1" 445 x 445 N/2.5 cm FS 5134 / ASTM D2261 Adhesion 26 lbs./2" 116 N/5 cm FS 5970 / ASTM D751 Cold Crack -30° F -34° C FS 5874 / ASTM D2136 Treatments Anti-Mildew, UV Pigments Fire Retardant Self Extinguishing Finish Matte	Weight	18.5 oz./yd²	627 g/m2	FS 5040 / ASTM D3776
Grab Tensile 375 x 375 lbs./1" 1668 x 1668 N/2.5 cm FS 5100 / ASTM D5034 Tongue Tear 100 x 100 lbs./1" 445 x 445 N/2.5 cm FS 5134 / ASTM D2261 Adhesion 26 lbs./2" 116 N/5 cm FS 5970 / ASTM D751 Cold Crack -30° F -34° C FS 5874 / ASTM D2136 Treatments Anti-Mildew, UV Pigments Fire Retardant Self Extinguishing Finish Matte	Widths	up to 126"	up to 320 cm	-
Tongue Tear 100 x 100 lbs./1" 445 x 445 N/2.5 cm FS 5134 / ASTM D2261 Adhesion 26 lbs./2" 116 N/5 cm FS 5970 / ASTM D751 Cold Crack -30° F -34° C FS 5874 / ASTM D2136 Treatments Anti-Mildew, UV Pigments Fire Retardant Self Extinguishing Finish Matte	Construction	18 x 17/1"	7 x 7/cm by 1100 x 1430	-
Adhesion 26 lbs./2" 116 N/5 cm FS 5970 / ASTM D751 Cold Crack -30° F -34° C FS 5874 / ASTM D2136 Treatments Anti-Mildew, UV Pigments Fire Retardant Self Extinguishing Finish Matte	Grab Tensile	375 x 375 lbs./1"	1668 x 1668 N/2.5 cm	FS 5100 / ASTM D5034
Cold Crack -30° F -34° C FS 5874 / ASTM D2136 Treatments Anti-Mildew, UV Pigments Fire Retardant Self Extinguishing Finish Matte	Tongue Tear	100 x 100 lbs./1"	445 x 445 N/2.5 cm	FS 5134 / ASTM D2261
Treatments Anti-Mildew, UV Pigments Fire Retardant Self Extinguishing Finish Matte	Adhesion	26 lbs./2"	116 N/5 cm	FS 5970 / ASTM D751
Fire Retardant Self Extinguishing Finish Matte	Cold Crack	-30° F	-34° C	FS 5874 / ASTM D2136
Finish Matte	Treatments		Anti-Mildew, UV Pigmer	nts
	Fire Retardant		Self Extinguishing	
Put-Up 75 yds. 69 m	Finish		Matte	
	Put-Up	75 yds.	69 m.	-