

Ultra-Spill Pallets

Pull Over Cover Specifications: 13 oz. laminated

Material Description - Base Fabric							
Fiber	Polyester						
Thickness	.019" (0.48 m/m)						
Yarn (Denier)	9/9 (fd/inch)						
Fabric Count (threads)	100 yards						
Type of Coating	S-PVC						

Physical Properties									
					Test Method				
		English	Metric	FS-191	ASTM	DIN			
Tensile Strength	Warp	185 lbs/2"	84.1 kg/5cm	FS 5102	ASTM D 5035	DIN 53354			
(Strip Method)	Fill	167 lbs/2"	75.9 kg/5cm						
Tear Strength	Warp	40 lbs	18.2 kg	FS 5134	ASTM D 2261	DIN 53356			
(Tongue Method)	Fill	43 lbs	19.5 kg						
Adhesion Strength		22 lbs/2"		FS 5970	ASTM D 2724				
Temperature Resistance		-22 ~ +160⁰F	-30 ~ +70⁰C		ASTM D 2136	DIN 53361			
Special Features	UV For Exterior Applications, Mildew Resistant. NFPA-701 Fire Rated								

Note: The information contained herein is believed to be reliable but no representations, guarantees or warrantees of any kind are made as to its accuracy or suitability for particular applications.