STAINLESS STEEL



WESCO STAINLESS STEEL SHELF CARTS

- 430 stainless steel shelf and frame construction.
- NSF Approved.
- 4 swivel, zinc plated casters with non-marking rubber tread polyurethane hub wheels.
- Three shelves:
 - .040" thick
 - top and center 1" lip, 3 sides
 - bottom, flat, no lip.
- Welded construction.
- Protection bumpers on legs and handle.
- Shelves have reinforced hemmed front.
- Overall capacity based upon evenly distributed loads.*





| Part # Model # | 260290 SS3C11 | 260291 SS3C22 | 260292 SS4C11 | 260293 SS4C22 | 260294 SS4C44 |
|--------------------------|--------------------|-------------------|--------------------------|----------------------|--------------------------|
| *Overall Capacity | 300 lbs | 300 lbs | 500 lbs | 500 lbs | 500 lbs |
| Capacity Per Shelf | 100 lbs | 100 lbs | 166 lbs | 166 lbs | 166 lbs |
| Shelf Size (L x W) | 24" x 15.5" | 27.125" x 17.625" | 24" x 15.75" | 27.375" x 18" | 35.125" x 21" |
| Shelf Lip Height | 1" | 1" | 1" | 1" | 1" |
| Distance Between Shelves | 12.75" | 13.25" | 12.5" top/14.625" bottom | 13" top/14.5" bottom | 14.375" top/14.5" bottom |
| Caster Wheel | 3.5" dia. x .75" W | 3.5" dia75" W | 4" dia. x .75" W | 4" dia. x .75" W | 5" dia. x 1.25" W |
| Weight | 30.5 lbs | 40 lbs | 36 lbs | 42 lbs | 67 lbs |



WESCO STAINLESS STEEL MANUAL HIGH LIFTS

- 1 year pump warranty.
- 304 stainless steel construction. Forks are 316 stainless steel.
- Nylon 3" load (WHL-2) and 8"nylon steering (WHL-1) wheels.
- 180° steering arc.
- Loop handles with inside hand control.
- Closed pallets must be placed on top of forks.
- 6 1/2" wide forks.
- Overload bypass.
- Two stage pump: number of strokes to full height (unloaded): Standard - 69. Quick Lift - 28.




QUICK LIFT setting allows operator to raise the height of the lift with fewer strokes.

WESCO STAINLESS STEEL ELECTRIC HIGH LIFTS

- 1 year pump warranty.
- 304 stainless steel construction. Forks are 316 stainless steel.
- Nylon 3" load (WHL-2) and 8"nylon steering (WHL-1) wheels.
- 12 volt battery charger included.
- 10-12 second lift time unloaded.
- Overload bypass.
- 180° steering radius.
- 6 1/2" wide forks.
- Telescoping pump piston.





Manual High Lift

Part #272859 / Model #SSTHL27M

Electric High Lift Part #272860 / Model #SSTHL27E

H-1



H-2 Lowered Height

H-3 Raised Height

WHL-2 Load Wheel Diameter

L-2

WESCO 304 STAINLESS STEEL PALLET TRUCK

- 1 year pump warranty.
- 304 stainless construction.
- For use in food industry and areas where water or other corrosive solutions are needed.
- 6 1/4" wide forks.
- 7" nylon steering wheels.
- 3" nylon load wheels.
- Nylon entry roller.
- Comfort-grip coated handle.
- 210° steering radius.

| Part # Model # | 272152 SSPT |
|-------------------|--------------------|
| Capacity | 5,500 lbs |
| W-1 x L-1 | 27" x 48" |
| W-2 | 6.25" |
| L-2 | 62.5" |
| WHL-1 / WHL-2 | 7" / 3" |
| H-1 / H-2 / H-3 | 47.5" / 3" / 7.25" |
| Weight | 164lbs |



WESCO 304 STAINLESS STEEL HYDRAULIC PEDALIFT

■ 1 Year Parts Warranty.

- Wesco Manufactured Hydraulic Jack -Over 40 Years of Proven Quality.
- 4-wheeled model.
- 304 stainless steel construction including hydraulic pump body, lift piston, and wheel lock. Foot operated hydraulic pump raises platform, foot release lowers platform and controls lowering speed.
- Platform sits 5.75" above floor.
- Wheel lock standard.
- 60.5" overall height.
- 8" x 2" polyurethane tread on polypropylene hub, non-marking wheels with 440 stainless sealed 3/4" precision ball bearing.
- 304 stainless swivel casters with plain bore 3.5" hard rubber wheels.



| Part # | 260186 | 260197 |
|------------------------|-----------------------|------------------|
| Model # | SSDPL-54-2222 | SSDPL-54-F |
| Capacity | 750 lbs | 750 lbs |
| Platform or Fork W x L | Platform 22" x 22" | Fork 3" x 18" |
| Lift Height | 54" | 54" |
| Load Center | 10" | 10" |
| Lowered Height | 5.75" | 5.75" |
| Weight | 175 lbs | 181 lbs |



4-Wheeled Pedalift Part #260197 Model #SSDPL-54-F

WESCO 304 STAINLESS STEEL HYDRAULIC DRUM LIFTER

- 1 Year Parts Warranty.
- Wesco Manufactured Hydraulic Jack -Over 40 Years of Proven Quality.
- Lifts, transports, and places drums on spill or standard pallets.
- 304 stainless auto grab drum clamp with manual lock down knob.
- 304 stainless steel construction including hydraulic pump body, lift piston, and floor lock. Foot operated hydraulic pump raises drum, foot release lowers drum and controls lowering speed.
- (2) 5" x 2" black phenolic wheels with 304 stainless roller bearing.
- (2) 304 stainless swivel casters with 5" x 2" black phenolic wheels, 304 stainless bearings, NSF certified washdown casters.
- Handles most 30, 55 or 85 gallon drums Steel, Fiber and Poly.
- Works with most drums with locking rings.
- Lift range: 26"-73" at lifting clamp.
- Single position outriggers non-telescoping.



Drum Handler Part #240240 / Model #SSDH

| Part # Model # | 240240 SSDH |
|-------------------|----------------|
| Capacity | 800 lbs |
| Rise/Stroke | 1" |
| Weight | 207 lbs |

WESCO 304 STAINLESS STEEL DRUM/HAND TRUCK

- 304 stainless steel construction.
- Utility of a hand truck & drum truck.
- Chime hook works with 55 and 30 gallon drums.
- Curved frame holds 5-gallon pails and kegs.
- With noseplate resting flat on floor, 18" to center of lowered chime hook.
- Noseplate 7.812" D x 14" W.
- 8" x 2" polyurethane tread on polypropylene hub, non-marking wheels with 440 stainless sealed 3/4" precision ball bearing.



Drum / Hand Truck Part #210352 / Model #156DH-PP8-SS

| Part # | 210351 | 210352 |
|------------|----------------|----------------|
| Model # | 156-PP8-SS | 156DH-PP8-SS |
| Capacity | 600 lbs | 600 lbs |
| Wheel Type | 8" non-marking | 8" non-marking |
| Weight | 33 lbs | 33.5 lbs |

WESCO 304 STAINLESS STEEL HAND TRUCK

- 304 stainless steel construction.
- Swept back continuous handle with curved back design.
- Versatile frame design allows one or two hand control.
- Four horizontal cross straps and vertical center strap provide support for small packages.
- 8" x 2" polyurethane tread on polypropylene hub, non-marking wheels with 440 stainless sealed 3/4" precision ball bearing.



Hand Truck Part #210351 / Model #156-PP8-SS

WESCO 304 STAINLESS STEEL FOLDING HANDLE TRUCK

- 304 stainless steel construction.
- Fold down handle for easy storage.
- Caster: sealed bearing with stainless rig.
- TPR rubber non-marking caster wheels.
- Vinyl perimeter bumper.
- Boxed and UPS shippable.

| Part # | 270457 | 270458 |
|---------------|-------------------|--------------------------------|
| Model # | Deluxe | Deluxe |
| Capacity | 440 lbs | 770 lbs |
| Platform Size | 19" x 29" | 22.5" x 34" |
| Caster Size | 2 swivel/2 rigid | 2 swivel/2 rigid |
| | 4" Stainless Rigs | 4" <mark>Stainless</mark> Rigs |
| Handle Height | 34.5" | 34" |
| Weight | 26 lbs | 37 lbs |



WESCO HEAVY DUTY 304 STAINLESS STEEL FAUCET

- 304 stainless steel.
- Adjustable shank designed to easily adjust to proper drain position after installing in drum.
- .75" NPT connection.
- PTFE gasket.
- 1.50 lbs.



Part# 272038
Internal flame arrestor.
FM APPROVED for use
with oils (under 30 SAE) and
non flammables, compatible
with stainless steel.

WESCO 304 STAINLESS STEEL ROTARY PUMP

- Made from corrosion resistant materials
- 304 stainless steel pump body.
- 304 stainless steel dispensing spout.
- 304 stainless steel 3 piece suction tube.
- PTFE vanes.
- UPS shippable.
- Compatible fluids: solvents, oils, mild corrosives.
- Min./ Max. temperature rating: 40° Fahrenheit / 140° Fahrenheit.
- 2" NPT Bung Adapter fits 15, 30 and 55 gallon drums.
- ALWAYS USE A GROUND WIRE.
- Weight: 13 lbs.



WESCO 304 STAINLESS STEEL DRUM DOLLIES

■ Wesco's Stability Advantage.

By design, Wesco casters are mounted past the dolly and drum rim. Our casters are mounted further apart than standard designs with casters completely underneath the drum and closer together. The further the casters are apart the greater the stability.

- Welded 304 stainless steel dolly construction with reinforced outriggers.
- 304 stainless dollies are ideal for clean room, pharmaceutical, food, and wash down applications.
- Models available for 30, 55, and 85 gallon drums.
- Three caster set options:


HRZ: zinc plated swivel rig with 3" hard rubber wheel & zinc plated hardware. *HRSS: 304 stainless steel swivel rig with 3" hard rubber wheel and stainless hardware.

*PPSS: 304 stainless steel swivel rig with 3" white polypropylene wheel and stainless hardware.

*Suitable for wash down applications.



Drum Dolly
Part #240197 / Model #SS5-PPSS
All stainless rigs with
3" polypropylene wheels



| Part # | 240192 | 240193 | 240194 |
|-----------------------|------------------------|-----------------------|------------------------|
| Model # | SS3-HRZ | SS3-HRSS | SS3-PPSS |
| Capacity | 900 lbs | 900 lbs | 1,000 lbs |
| I.D. | 19" | 19" | 19" |
| Drum Size | 30 gal | 30 gal | 30 gal |
| Caster Rig | Zinc plate 4 swivel | Stainless 4 swivel | Stainless 4 swivel |
| 3" Caster Wheel | Hard Rubber | Hard Rubber | White Polypropylene |
| Dolly Material | 304 Stainless | 304 Stainless | 304 Stainless |
| Weight | 20 lbs | 20 lbs | 18 lbs |

| Part # | 240195 | 240196 | 240197 | 240198 | 240199 | 240200 |
|-----------------|------------------------|-----------------------|------------------------|------------------------|-----------------------|------------------------|
| Model # | SS5-HRZ | SS5-HRSS | SS5-PPSS | SS8-HRZ | SS8-HRSS | SS8-PPSS |
| Capacity | 900 lbs | 900 lbs | 1,000 lbs | 900 lbs | 900 lbs | 1,000 lbs |
| I.D. | 24" | 24" | 24" | 27" | 27" | 27" |
| Drum Size | 55 gal | 55 gal | 55 gal | 85 gal | 85 gal | 85 gal |
| Caster Rig | Zinc plate 4 swivel | Stainless 4 swivel | Stainless 4 swivel | Zinc plate 4 swivel | Stainless 4 swivel | Stainless 4 swivel |
| 3" Caster Wheel | Hard Rubber | Hard Rubber | White Polypropylene | Hard Rubber | Hard Rubber | White Polypropylene |
| Dolly Material | 304 Stainless | 304 Stainless | 304 Stainless | 304 Stainless | 304 Stainless | 304 Stainless |
| Weight | 22 lbs | 22 lbs | 21 lbs | 24 lbs | 24 lbs | 23 lbs |

WESCO STAINLESS STEEL KNOCKDOWN (KD)DRUM TRUCKS

- US Patent No. 9,302,688.
- UPS shippable KD and boxed.
- Two models: 304 stainless construction to handle steel and poly drums.
- Handles 30, 55 and 85 gallon drums.
- Requires minimal assembly.
- All parts removable and interchangeable among all models.
- Each of the models includes handle, frame, base, kickstand, axle, toes or feet, wheel, chime hook or belt and hardware.
- Foot operated break-over assist bar provides extra leverage to tilt and balance the load.
- Stainless models okay for wash down.
- Optional 3rd Wheel (#240211):
 - Allows load to stand in tilted position.
 - Ergonomic design, better maneuverability.
 - Better load support.
 - Helps reduce breakover effort.
 - 5" x 2" swivel caster.
 - 14 lbs.
- Milled toes are hard-faced, double-beveled.





Part #240019 Model #KD-SS-STL-PO Shown with optional 3rd wheel







| Part # | 240019 | 240020 | |
|------------------------|------------------------------|----------------------------|--|
| Model # | KD-SS-STL-PO | KD-SS-POLY-PO | |
| Capacity | 1,000 lbs | 1,000 lbs | |
| Wheel | 10" Polyolefin | 10" Polyolefin | |
| Drum Type Handled | Steel | Poly | |
| Toe/Foot (replaceable) | Stainless Milled Toe #051904 | Stainless Foot #050362 | |
| Construction | 304 Stainless | 304 Stainless | |
| Chime Hook | #050197- stainless | N/A | |
| Belt | N/A | #240213 - stainless buckle | |
| Weight | 66 lbs | 75 lbs | |

WESCO 304 STAINLESS STEEL UNIVERSAL DRUM LIFTER

- 304 stainless steel construction.
- Design allows for the loading of drums into overpacks with use of hoist.
- Works on open and closed head drums.
- For use with standard steel or poly drums with at least a 3/16" chime.
- Lifting arms are adjustable to work with most 55 or 30 gallon drums.
- Three-point contact of the lifting arms prevents or minimizes deformation of the drum and provides more secure lifting.
- 1,000 lb. capacity.
- Weight 21 lbs.



Distributed by:



For more details on this equipment or for information regarding any of the products available from WESCO Industrial products, Inc., please contact your authorized dealer. Part #179021